1-1337653 -0 Product Details

Live Product Chat US Only 8:30am - 5pm ET, Mon - Fri

No Image Available

1-1337653 -0

Active

UHF/ Miniature UHF, RF Connectors

Converted to EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- Connector
- Jack
- Terminate To Coaxial Cable
- Without Snap-Lock
- Coaxial Cable Termination Type = Solder/Clamp

View all Features | Find Similar Products

Quick Links

Check Pricing & Availability
Search for Tooling
Product Feature Selector
Contact Us About This Product

Documentation & Additional Information

Product Drawings:

- UHF STRAIGHT JACK SOLDER RG9B/U, 214/U, URM91, KX13... (PDF, English)

Catalog Pages/Data Sheets:

- None Available

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files:

- None Available

List all Documents

Additional Information:

- Product Line Information

Related Products:

- Tooling

Product Features

(Please use the Product Drawing for all design activity)

Product Type Features:

- Product Type = Connector
- Gender = Jack
- Body Size = Standard
- Dielectric Material = PTFE
- Rubber Gasket = With
- Body Style = Straight
- Grade = Professional
- Body Material = Brass
- Sealed = No
- Isolated = No
- Gasket Material = White Silicone Rubber
- Flats Dimension = 16.0 A/F

Mechanical Attachment:

- Panel Attachment = Without

Electrical Characteristics:

- Connector Impedance (?) = Non-Constant

Termination Related Features:

- Coaxial Cable Termination Type = Solder/Clamp

Body Related Features:

- Snap-Lock = Without
- Body Plating = Nickel
- Polarized = No

Contact Related Features:

- Center Contact Plating = Gold
- Contact Material = Brass

Configuration Related Features:

- Coaxial Cable Type (RG/U or Mfg.) = 214, 9B, Raychem 5012A3422, Raychem 5012F3332, Raychem 5012F3832, Raychem 5012M3612, URM 91

Industry Standards:

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Converted to comply with RoHS directive

Conditions for Usage:

- Terminate To = Coaxial Cable
- Operating Temperature (Max.) (°C) = 165

Packaging Related Features:

- Packaging Method = Individual
- Packaging Quantity = 25

Other:

- Brand = Greenpar

© 2008 Tyco Electronics Corporation All Rights Reserved