



188LMB200M2EG
SNAP-IN/ SNAP MOUNT
Parts are RoHS compliant
Date code when parts became RoHS: 1404

Capacitance: 1800 uF
Dissipation Factor: 0.15 Max at 120 Hz and 20°C
Temperature Range: -25°C to +105°C
Impedance: N/A

Tolerance: -20 %, +20 %
WVDC: 200 Volts DC
SVDC: 250 Volts DC
Ripple Current: 3.48 A at 120 Hz and 105°C
Impedance Ratios:-25°C/20°C 8 and -40°C/20°C --

Frequency Multipliers:

50 HZ	120 HZ	400 HZ	1 KHZ	10 KHZ	100 KHZ
0.8	1	1	1.25	1.47	1.47

Temperature Multipliers:

45°C	60°C	70°C	65°C	75°C	85°C	105°C	125°C
2	1.9	1.7	1.8	1.4	1.4	1	0

Diameter (D): 35 mm + 1 mm
Length (L): 45 mm + 2 mm
Coating: BrownPET sleeving

Lead Wire Diameter (d): 1.5 mm +/- 0.5 mm
Lead Length: 4 mm +/- 1 mm
Lead Finish: Matte Tin



188LMB200M2EG
SNAP-IN/ SNAP MOUNT
Parts are RoHS compliant
Date code when parts became RoHS: 1404

Capacitance: 1800 uF
Dissipation Factor: 0.15 Max at 120 Hz and 20°C
Temperature Range: -25°C to +105°C
Impedance: N/A

Tolerance: -20 %, +20 %
WVDC: 200 Volts DC
SVDC: 250 Volts DC
Ripple Current: 3.48 A at 120 Hz and 105°C
Impedance Ratios:-25°C/20°C 8 and -40°C/20°C --

Frequency Multipliers:

50 HZ	120 HZ	400 HZ	1 KHZ	10 KHZ	100 KHZ
0.8	1	1	1.25	1.47	1.47

Temperature Multipliers:

45°C	60°C	70°C	65°C	75°C	85°C	105°C	125°C
2	1.9	1.7	1.8	1.4	1.4	1	0

Diameter (D): 35 mm + 1 mm
Length (L): 45 mm + 2 mm
Coating: BrownPET sleeving

Lead Wire Diameter (d): 1.5 mm +/- 0.5 mm
Lead Length: 4 mm +/- 1 mm
Lead Finish: Matte Tin

