


SKKE 380



Rectifier Diode Modules

SKKE 380

Features

- Heat transfer through aluminium nitride ceramic isolated metal baseplate
- Precisious metal pressure contacts for high reliability
- UL recognized, file no. E 63 53

Typical Applications

- Line rectifiers for transistorized AC motor controllers
- Field supply for DC motors

1) The screws must be lubricated

V_{RSM} V	V_{RRM} V	$I_{FRMS} = 600\text{ A}$ (maximum value for continuous operation) $I_{FAV} = 380\text{ A}$ (sin. 180; $T_c = 100\text{ °C}$)		
1300	1200	SKKE 380/12		
1700	1600	SKKE 380/16		

Symbol	Conditions	Values	Units
I_{FAV}	sin. 180; $T_c = 100\text{ °C}$	380	A
I_{FSM}	$T_{vj} = 25\text{ °C}$; 10 ms	11000	A
	$T_{vj} = 150\text{ °C}$; 10 ms	10000	A
i^2t	$T_{vj} = 25\text{ °C}$; 8,3 ... 10 ms	605000	A²s
	$T_{vj} = 150\text{ °C}$; 8,3 ... 10 ms	500000	A²s
V_F	$T_{vj} = 25\text{ °C}$; $I_F = 1000\text{ A}$	max. 1,25	V
$V_{(TO)}$	$T_{vj} = 150\text{ °C}$	max. 0,8	V
r_T	$T_{vj} = 150\text{ °C}$	max. 0,35	mΩ
I_{RD}	$T_{vj} = 150\text{ °C}$; $V_{RD} = V_{RRM}$	max. 15	mA
$R_{th(j-c)}$	cont.; per diode = per module	0,11	K/W
	sin. 180; per diode = per module	0,116	K/W
$R_{th(c-s)}$	per diode = per module	0,04	K/W
T_{vj}		- 40 ... + 150	°C
T_{stg}		- 40 ... + 130	°C
V_{isol}	a. c. 50 Hz; r.m.s.; 1 s / 1 min.	3600 / 3000	V~
M_s	to heatsink	5 ± 15 %	Nm
M_t	to terminals	9 ± 15 % ¹⁾	Nm
a		5 * 9,81	m/s²
m	approx.	550	g
Case		A 77b	






Fig. 11L Power dissipation per diode vs. forward current




Fig. 11R Power dissipation per diode vs. ambient temperature




Fig. 14 Transient thermal impedance vs. time




Fig. 15 Forward characteristics





Fig. 16 Surge overload current vs. time



This technical information specifies semiconductor devices but promises no characteristics. No warranty or guarantee expressed or implied is made regarding delivery, performance or suitability.