



## 256MHBS45K2J

DC LINK

Parts are RoHS compliant

**APPLICATIONS:** DC link, Switching power supplies, induction heaters, Motor speed controls

### ELECTRICAL SPECIFICATIONS

**Capacitance:** 25  $\mu$ F

**Dissipation Factor:** 0.0014 Max at 1000 Hz and 25°C

**Temperature Coefficient:** -200 PPM/°C: -100 PPM/°C, 100 PPM/°C

**Ripple Current:** 14 A at 10 kHz - 45 kHz and +95°C

**ESR:** 4.3 milliOhms (typical) at 100 kHz and 25°C

**Self Inductance:** 1 Nanohenries maximum per mm of pitch

**dvdt:** 24 V/ $\mu$ s

**Tolerance:** -10 % , +10 %

**Temperature Range:** -40°C to +100°C

Above 85°C the rated (DC/AC) voltage must be derated at per 1.5%/°C

**WVDC:** 800 Volts DC

**SVDC:** 920 Volts DC

**VAC:** 315 Volts AC

**Terminal to Terminal Dielectric strength:** 1.6 times the rated DC voltage when applied between the terminals for 60 seconds

**Terminal to case Dielectric strength:** 3000 VAC when applied between the terminals and case for 60 seconds

**Insulation Resistance (Terminal to Terminal):** 3000 MINIMUM after 100 Volts DC is applied for 60 seconds at 20°C

**Insulation resistance (Terminal to Case):** N/A Megohms MINIMUM after 0 Volts DC is applied for 0 seconds at 0

**Reliability:** 300 failures/billion component hours

**Load Life:** 60000 hours at 70°C with 100% of rated voltage

**Capacitance Change:** 0 of initially measured value

**D.F. Change:** 0 of maximum specified value

**I.R. Change:** 0 of minimum specified value


### PHYSICAL DIMENSIONS

**Length (L):** 42.5 mm, 1 mm

**Height (H):** 45 mm, +/-1 mm

**Thickness (T):** 30 mm, +/- .6 mm

**Lead Spacing (S):** 37.5 mm, +/-0.4 mm



2400 East Devon Avenue Suite 292 Des Plaines, IL 60018 (847) 675-1760 FAX (847) 673-2850

Illinois Capacitor (HK) Ltd., Tel: 85227930931, Fax: 85227930731, [www.ilcap.com.hk](http://www.ilcap.com.hk)

© Copyright 2020 Illinois Capacitor. An affiliate of Cornell Dubilier, All Rights Reserved