

## 827ULR2R5MFF

RADIAL LEAD ALUMINUM POLYMER CAPACITORS

Parts are RoHS compliant

### ELECTRICAL SPECIFICATIONS

Capacitance: 820  $\mu$ F

Dissipation Factor: 0.1 Max at 120 Hz and 20°C

Temperature Range: -55°C to +105°C

ESR: 0.2 Ohms Max at 20°C and 120 Hz

Impedance: 7 milliohm Max at 20°C and 100 KHz

Tolerance: -20 %, +20 %

WVDC: 2.5 Volts DC

SVDC: 2.875 Volts DC

Ripple Current: 6100 mA at 100 kHz and 105°C

N/A

Impedance Ratios: -55°C/20°C  $\leq$  1.25 and +105°C/20°C  $\leq$  1.25

Leakage Current: 0.2CV

410  $\mu$ A after 2 Minutes

Load Life: 2000 hours at 105°C with 100 % of rated voltage and with 0 % of rated ripple current

Capacitance Change:  $\leq$ 20% of initial measured value

Dissipation Factor Change:  $\leq$ 150% of maximum specified value

ESR Change: N/A

Leakage Current:  $\leq$ 100% of maximum specified value

### Ripple Current Multipliers

#### Frequency Multipliers:

| 50 HZ | 120 HZ | 400 HZ | 1 KHZ | 10 KHZ | 100 KHZ |
|-------|--------|--------|-------|--------|---------|
| 0.05  | 0.05   | 0.05   | 0.3   | 0.7    | 1       |

#### Temperature Multipliers:

| 45°C | 60°C | 70°C | 65°C | 75°C | 85°C | 105°C | 125°C |
|------|------|------|------|------|------|-------|-------|
| 2    | 1.9  | 1.7  | 1.8  | 1.4  | 1.4  | 1     | 0     |

### PHYSICAL DIMENSIONS

Diameter (D): 8 mm + .5 mm

Length (L): 8 mm + 1 mm


Lead Spacing (S): 3.5 mm +/- 0.5 mm

Coating: clearlaminate sleeving

Lead Wire Diameter (d): 0.6 mm +/- 0.05 mm

Lead Length: 15 mm +/- Min mm

Lead Finish: Matte Tin



2400 East Devon Avenue Suite 292 Des Plaines, IL 60018 (847) 675-1760 FAX (847) 673-2850

Illinois Capacitor (HK) Ltd., Tel: 85227930931, Fax: 85227930731, [www.illcap.com.hk](http://www.illcap.com.hk)

© Copyright 2020 Illinois Capacitor. An affiliate of Cornell Dubilier, All Rights Reserved