






### FIELD-REPLACEABLE CONTACTS (For universal receptacle)


These accessories have been specifically designed for the adjustment at the rear of hermetically sealed universal receptacles.

The choice of their dimensions depends on the PCB or on the thickness of the MIC box. Moreover these contacts and insulators are also compatible with SMA UNIVERSAL RECEPTACLES.



| Part number   | Fig. | A    | Packaging | Note              | Associated insulator P/N |
|---------------|------|------|-----------|-------------------|--------------------------|
| R280 460 000  | 1    | 1.77 | 10        | Flat tab          | R280 467 0000            |
| R280 461 000  | 1    | 3.37 |           | Flat tab          | R280 468 0000            |
| R280 462 000  | 2    | 1.77 |           | Cylindrical tab   | R280 467 0000            |
| R280 463 000  | 2    | 3.37 |           | Cylindrical tab   | R280 468 0000            |
| R280 464 000* | 3    |      |           | Symetrical        | N/A                      |
| R280 465 000  | 4    |      |           | Flat recessed tab | N/A                      |

### FIELD-REPLACEABLE INSULATORS



| Part number  | A    | Packaging |
|--------------|------|-----------|
| R280 467 000 | 1.57 | 10        |
| R280 468 000 | 3.17 | 10        |

\* Upon request