






## PLUGS

## UNINSULATED BANANA PLUGS

| FIGURE                                                                                                                                                                              | PART NUMBER  | DESCRIPTION                                                                                                                                                                                                    | PANEL DRILLING |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|
|  <br>(B4)         | R941 019 000 | <b>Solder or crimp</b><br><b>1.5 mm solder post</b><br>Strip length: 5 mm<br>Crimp tool: Buchanan R612 548 000<br>Positioner Radiall R282 561 000<br>Crimp setting: 1.20 (18 AWG)<br>1.08 (22 AWG)<br>Maxi 15A |                |
|  <br>(B4)         | R941 029 000 | <b>Solder or crimp</b><br><b>2 mm solder post</b><br>Strip length: 5 mm<br>Crimp tool: Buchanan R612 548 000<br>Positioner Radiall R282 561 000<br>Crimp setting: 1.50 (14 AWG)<br>1.25 (18 AWG)               |                |
|  <br>(B4-8 ISO)   | R941 049 000 | <b>Threaded panel connection</b><br>8 mm rear length                                                                                                                                                           | P03            |
|  <br>(B4-8 ISO) | R941 069 000 | <b>Threaded panel connection</b><br>18 mm rear length                                                                                                                                                          | P03            |
|               | R941 149 000 | <b>Panel banana plug</b><br>4 mm with rear socket<br>for mating with 4 mm plug                                                                                                                                 | P01            |

## INSULATED BANANA PLUGS

| FIGURE                                                                                        | PART NUMBER  | COLOR  | REAR TERMINATION OPTIONS                                                                              |
|-----------------------------------------------------------------------------------------------|--------------|--------|-------------------------------------------------------------------------------------------------------|
| <br>(B1)   | R941 330 000 | Black  | - Tin-plated solder cup or<br>- Rear socket for 2 mm banana plug<br>(14 AWG)                          |
|                                                                                               | R941 331 000 | Red    |                                                                                                       |
|                                                                                               | R941 332 000 | Green  |                                                                                                       |
|                                                                                               | R941 333 000 | Blue   |                                                                                                       |
|                                                                                               | R941 334 000 | Yellow |                                                                                                       |
|                                                                                               | R941 336 000 | White  |                                                                                                       |
| <br>(B2)   | R941 340 000 | Black  | - Tin-plated solder cup or<br>- Screw tightening or<br>- Rear socket for 2 mm banana plug<br>(14 AWG) |
|                                                                                               | R941 341 000 | Red    |                                                                                                       |
|                                                                                               | R941 342 000 | Green  |                                                                                                       |
|                                                                                               | R941 343 000 | Blue   |                                                                                                       |
|                                                                                               | R941 344 000 | Yellow |                                                                                                       |
|                                                                                               | R941 346 000 | White  |                                                                                                       |
| <br>(BDR4) | R941 460 000 | Black  | - Stackable banana with quick-grip clamp for stripped cable<br>- 2 & 4 mm socket for banana plugs     |
|                                                                                               | R941 461 000 | Red    |                                                                                                       |

To download data sheets, visit [www.radiall.com](http://www.radiall.com)  
 For other specific demand, please contact Radiall sales

[www.radiall.com](http://www.radiall.com)