

DATASHEET

1.85mm(F) to 1.85mm(F) 4 Hole Adapter

Product Name

1. 1P85F4H-1P85F-001





1.85mm(F) to 1.85mm(F) 4 Hole Adapter

Document No.	CRD-DS-2251-05
Date / Rev.	01.Jun.2023 / 1
Confidential level	N/A

1. Product

1-1. 1.85mm(F) to 1.85mm(F) 4 Hole Adapter
(P/N : 1P85F4H-1P85F-001)

2. Specifications

2-1. Material

Body : Stainless Steel, Passivated
Center Conductor : BeCu, Au Plated
Insulator : PS

2-2. Environmental

Operating Temperature : -50°C to 100°C

2-3. Electrical

Impedance : 50Ω Typ.
Operating Freq. : DC to 67GHz
VSWR : 1.25 : 1 @67GHz Typ.
1.30 : 1 @67GHz Max.
Insertion Loss : $-0.05\text{dB} \times \sqrt{f}$
RF Leakage : -100dB



3. Drawing

3-1. 1.85mm(F) to 1.85mm(F) 4 Hole Adapter

(P/N : 1P85F4H-1P85F-001)





Document No.	CRD-DS-2251-05
Date / Rev.	01.Jun.2023 / 1
Confidential level	N/A

4. Data

4-1. 1.85mm(F) to 1.85mm(F) 4 Hole Adapter

(P/N : 1P85F4H-1P85F-001)

