




MARKETING SALES DRAWING

DIMENSIONS IN INCHES - DO NOT SCALE THIS DRAWING
DIMENSIONS IN METRIC - []

This drawing is the property of
Tusonix, Inc., and may not be
used, reproduced, published or
disclosed to others without ex-
pressed authorization by Tusonix Inc.

Electrical Testing
per Tusonix standard
test plans and Mil-Std-202
Test Methods.



#20 (.032 [0.81]) AWG COPPER,
SILVER PLATED

SOLDER FILLET

.025 TYP.
[0.64 TYP.]

SOLDERABLE
AREA

.250
[6.35]

.165 MAX.
[4.20 MAX.]

.650 ±.015
[16.51 ±0.38]

.075 ±.010 DIA.
[1.91 ±0.25 DIA.]

SPECIFICATIONS

CAP. VALUE	1500 pF
CAP. TOL.	+100, -0%
TEMP. CHAR.	X5U
OPERATING TEMP.	-55° TO +125°C
OPERATING VOLT.	200 WVDC @ + 85°C
DIELECTRIC WITHSTANDING	400 VDC, 2 SEC.

NOTES:

- TUSONIX STANDARD PART NUMBER: 2463-002-X5U0-152P.
TUSONIX RoHS COMPLIANT PART
NUMBER: 2463-002-X5U0-152P LF.
CUSTOMER MUST SPECIFY STANDARD OR RoHS PART
NUMBER WHEN ORDERING.
- PART MARKING: STANDARD PART, NO MARKING.
RoHS PART: GREEN LABELING ON PACKAGING.

X-2015 Rev-0

REVISION RECORD				--TOLERANCES-- Unless Otherwise Specified		Title	
Original Release	0	19980305-3-03	ADDED NOTES & SILVER FINISH. S.M. 05-20-05	DECIMAL ±	.031 [0.79]	Drawn	S.M. 03-10-98
20050504-6-02	1	ADDED CIRCUIT & DIELECT. WITH: WVDC WAS 100. ADDED TOL TO DIM. .650. S.M. 08-19-05	2	ANGLES ±		Approved	J.Mc. 03-10-98
20050818-7-01	2	CHANGE DIM. .155 MAX TO .165 MAX	A	TUSONIX TUCSON, ARIZONA		SHOULDER FEED-THRU	
ECO-7202086							
				A		2463-002-X5U0-152P	