

DATASHEET

2.92mm(M) to 2.92mm(M) Adapter

Product Name

1. 2P92MST-2P92M-001





2.92mm(M) to 2.92mm(M) Adapter

Document No.	CRD-DS-2317-01
Date / Rev.	25.May.2023 / 1
Confidential level	N/A

1. Product

1-1. 2.92mm(M) to 2.92mm(M) Adapter

(P/N : 2P92MST-2P92M-001)

2. Specifications

2-1. Material

Coupling Nut : Stainless Steel, Passivated

Body : Stainless Steel, Passivated

Center Conductor : Brass, Au Plated

Insulator : PS

2-2. Environmental

Operating Temperature : -50°C to 100°C

2-3. Electrical

Impedance : 50Ω Typ.

Operating Freq. : DC to 40GHz

VSWR : 1.12 : 1 @40GHz Typ.

1.15 : 1 @40GHz Max.

Insertion Loss : -0.03dB x $\sqrt{f}$

RF Leakage : -100dB




2.92mm(M) to 2.92mm(M) Adapter

Document No.	CRD-DS-2317-01
Date / Rev.	25.May.2023 / 1
Confidential level	N/A

3. Drawing

3-1. 2.92mm(M) to 2.92mm(M) Adapter

(P/N : 2P92MST-2P92M-001)





2.92mm(M) to 2.92mm(M) Adapter

Document No.	CRD-DS-2317-01
Date / Rev.	25.May.2023 / 1
Confidential level	N/A

4. Data

4.1. 2.92mm(M) – 2.92mm(M) Adapter (P/N : 2P92MST-2P92M-001)

