

Sampling Phase Detectors

MSPD1011,MSPD1012,MSPD1013 Series

Data Sheet




Features

- Operating Frequency: 10 MHz to 20 GHz
- Surface mount package: 3.3 mm (L) x 2.8 mm (W) x 1.5 mm (H)
- RoHS Compliant

Applications

- Phase locked loops
- High frequency sampling



Description

The products of the MSPD101x-121 series are fully-contained sampling phase detectors, each comprising a beam lead silicon step recovery diode, beam lead DC blocking capacitors and a beam lead series-tee pair of low-barrier silicon Schottky diodes mounted on a ceramic substrate. The semiconductors and chip capacitors are protected with an epoxy encapsulation on the top side of the ceramic substrate. These products are manufactured using Aeroflex/Metelics proven diode fabrication and assembly processes which optimize diode characteristics for optimal electrical performance and excellent reliability.

These low profile, compact (3.3 mm L x 2.8 mm W x 1.5 mm H) surface mount components offer RF and microwave signal performance superior to comparable chip-and-wire discrete devices in leaded packages. These rugged devices are capable of reliable operation in all military, commercial and industrial applications. The MSPD101x-121 family of devices is RoHS compliant.

Environmental Capabilities


The MSPD101x-121 sampling phase detectors are capable of meeting the environmental requirements of MIL-STD-750 and MIL-STD-883.

ESD and Moisture Sensitivity Level Rating


As are all semiconductors, the MSPD101x-121 sampling phase detectors are susceptible to damage from ESD events. Proper ESD prevention procedures should be followed. The ESD rating for these devices is Class 0 (HBM). The moisture sensitivity level rating is MSL 1.



Sampling Phase Detector Schematic



CS121 Pinout



Pin Description

Pin Number	Description
1	Cathode terminal of step recovery diode
2	Anode terminal of step recovery diode
3	Cathode connection of Schottky diode series tee
4	Center node of Schottky diode series tee
5	Anode connection of Schottky diode series tee

Sampling Phase Detectors Data Sheet



Electrical Specifications

$T_A = 25^\circ\text{C}$ (Unless otherwise Defined)

Parameter	Condition	MSPD1011			MSPD1012			MSPD1013			Unit
		MIN	TYP	MAX	MIN	TYP	MAX	MIN	TYP	MAX	
Microwave signal level			-3 to 0			0 to 3			0 to 13		dBm
Schottky diode											
Barrier height			Low			Med.			High		
Forward voltage	$I_F = 1 \text{ mA}$	270		350	370		550	600		700	mV
Junction capacitance	$V_R = 0 \text{ V}, f = 1 \text{ MHz}$			0.1			0.1			0.1	pF
Total resistance	$I_F = 5 \text{ mA}$			24			24			24	
Step recovery diode											
Breakdown voltage	$I_R = 10 \text{ }\mu\text{A}$		20	30		20	30		20	30	V
Carrier life time	$I_F = 10 \text{ mA}, I_R = 6 \text{ mA}$		10			10			10		ns
Transition time	$I_F = 10 \text{ mA}, V_R = 10 \text{ V}$		70			70			70		ps
Junction capacitance	$V_R = 0 \text{ V}, f = 1 \text{ MHz}$			0.25			0.25			0.25	pF
DC block capacitor											
Capacitance	$f = 1 \text{ MHz}$		0.5	1		0.5	1		0.5	1	pF


Absolute Maximum Ratings

$T_A = +25^\circ\text{C}$ (Unless Otherwise Defined)

Parameter	Conditions	Absolute Maximum Value
RF Incident Power	Applied to step recovery diode (pin 1 to pin 2)	27 dBm
	Applied to microwave input (pin 4)	20 dBm
Operating Temperature		-55 °C to 125 °C
Storage Temperature		-65 °C to 150 °C
Junction Temperature		150 °C
Total Dissipated Power	Infinite heat sink, $T_{case} = 25^\circ\text{C}$. Derate power linearly from 100 mW @ 85 °C to 0 W @ 125 °C	100 mW

Typical Performance




$Z_0 = 50 \Omega$, $T_{CASE} = 25^\circ\text{C}$, (Unless Otherwise Defined)



The MSPD101x family of sampling phase detectors may be soldered to a printed circuit using conventional solder reflow or wave soldering procedures with RoHS type or Sn 60/Pb 40 type solders per the recommended time-temperature profile described in Table I and Figure 1.

Profile Feature	SnPb Solder Assembly	Pb-Free Solder Assembly
Average Ramp-Up Rate (T_L to T_P)	3°C /second maximum	3°C /second maximum
Preheat: - Temperature Min (T_{SMIN}) - Temperature Max (T_{SMAX}) - Time (min to max)(t_s)	100°C 150°C 60-120 s	150°C 200°C 60-180 s
T_{SMAX} to T_L - Ramp-Up Rate		3°C/s maximum
Time Maintained Above: - Temperature (T_L) - Time (t_L)	183°C 60-150 s	217°C 60-150 s
Peak temperature (T_P)	225 +0/-5°C	260 +0/-5°C
Time Within 5°C of Actual Peak Temperature (t_p)	10 – 30 s	20 – 40 s
Ramp-Down Rate	6°C /s maximum	6°C /s maximum
Time 25°C to Peak Temperature	6 minutes maximum	8 minutes maximum

Outline (CS121)




- NOTES:
1. SUBSTRATE MATERIAL: 10 MIL THICK 99.6% ALUMINA.
 2. COVER: BLACK CERAMIC.
 3. TOP SIDE AND BACKSIDE METALLIZATION: 500a TiW 3000A Au PLATING: 60u" ETCHABLE ELECTROLYTIC Ni/40u Au MIN
 4. PACKAGE INTERNAL VOLUME: 0.002151294 CC
 5. PHYSICAL INTERNAL VOLUME DEPENDENT UPON DIE SELECTION AND ATTACHMENT MATERIALS

All Dimensions in Inches

Sampling Phase Detectors Data Sheet






Recommended Circuit



Bill of Materials

Component	Reference Designator	Manufacturer	Manufacturer's Part Number	Quantity
Capacitor , 47 pF, 2%, 0603 pkg	C2,C3	Johanson Technology Inc	251R14S470JV4T	2
Capacitor , 22 pF, 2%, 0402 pkg	C5	Johanson Technology Inc	500R07S220GV4T	1
Capacitor , 10 pF, 2%, 0402 pkg	C1	Johanson Technology Inc	250R05L100GV4T	1
Capacitor , 39 pF, 2%, 0603 pkg	C4	Johanson Technology Inc	251R14S390GV4T	1
Inductor, 100 nH , 0603	L1,L2,L3	Coilcraft	0603CS-R10X-J-EU	3
Resistor, 100 Ω , 5%, 0.1 W, 0603	R1,R2	Panasonic Electronic Components	ERJ-3GEYJ101V	2
Sampling Phase Detector	U1	Aeroflex Metelics	MSPD101x-121	1
Connector, SMA Jack	J1,J2,J3	Cinch Connectivity Solutions Johnson	142-0761-871 (Digikey Part # J806-ND)	3
Transformer , 4:1 Balun,SM-22	T1	M/A COM	MABAES0061	1

Sampling Phase Detector Evaluation Board



Note

1. All dimensions in inches.
2. Circuit board material Rogers 4350B.

Part Number Ordering Information

Part Number	Description	Packaging
MSPD1011-121-T	Sampling Phase Detector, Low Barrier	Tube Packaging
MSPD1012-121-T	Sampling Phase Detector, Medium Barrier	
MSPD1013-121-T	Sampling Phase Detector, High Barrier	
MSPD1011-121-R	Sampling Phase Detector, Low Barrier	Tape & Reel Packaging Qty : 250 or 500 per reel
MSPD1012-121-R	Sampling Phase Detector, Medium Barrier	
MSPD1013-121-R	Sampling Phase Detector, High Barrier	
MSPD1011-121-W	Sampling Phase Detector, Low Barrier	Waffle Pack Packaging
MSPD1012-121-W	Sampling Phase Detector, Medium Barrier	
MSPD1013-121-W	Sampling Phase Detector, High Barrier	
MSPD1011-121-E	Sampling Phase Detector, Low Barrier Evaluation Board	Evaluation Board
MSPD1012-121-E	Sampling Phase Detector, Medium Barrier Evaluation Board	
MSPD1013-121-E	Sampling Phase Detector, High Barrier Evaluation Board	

Aeroflex / Metelics, Inc.

54 Grenier Field Road, Londonderry, NH 03053
Tel: (603) 641-3800
Sales: (888) 641-SEMI (7364)
Fax: (603)-641-3500

975 Stewart Drive, Sunnyvale, CA 94085
Tel: (408) 737-8181
Fax: (408) 733-7645

www.aeroflex.com/metelics

metelics-sales@eroflex.com

Aeroflex / Metelics, Inc. reserves the right to make changes to any products and services herein at any time without notice. Consult Aeroflex or an authorized sales representative to verify that the information in this data sheet is current before using this product. Aeroflex does not assume any responsibility or liability arising out of the application or use of any product or service described herein, except as expressly agreed to in writing by Aeroflex; nor does the purchase, lease, or use of a product or service from Aeroflex convey a license under any patent rights, copyrights, trademark rights, or any other of the intellectual rights of Aeroflex or of third parties.

Copyright 2012 Aeroflex / Metelics. All rights reserved.

ISO 9001:2008 certified companies



Our passion for performance is defined by three attributes represented by these three icons: solution-minded, performance-driven and customer-focused.