


40 Series

Ohmicone®, Silicone-Ceramic Conformal Axial Lead Wirewound Resistors 1% and 5% Tolerances Standard



Series	Wattage	Ohms	Dimensions (in. / mm)			Lead ga.
			Length	Diam.	Voltage	
41	1.0	0.10-6K	0.437 / 11.1	0.125 / 3.2	150	24
42	2.0	0.10-8K	0.406 / 10.3	0.219 / 5.6	100	20
43	3.0	0.10-20K	0.593 / 15.1	0.218 / 5.5	200	20
45	5.0	0.10-70K	0.937 / 23.8	0.343 / 8.7	460	18
47	7.0	0.10-80K	1.280 / 32.5	0.343 / 8.7	670	18
40	10.0	0.10-150K	1.642 / 41.7	0.406 / 10.3	1000	18

Non-Inductive versions available. Insert "N" before tolerance code. Example: 42NJ27R

Ohmite 40 Series resistors are the most economical conformal silicone-ceramic coated resistors offered. These all-welded units are characterized by their low temperature coefficients and resistance to thermal shock, making them ideal for a wide range of electrical and electronic applications.

Units with 1% and 5% tolerances are identical in construction and electrical specifications. Durable but economical 40 Series resistors exceed industry requirements for quality.

SPECIFICATIONS

Material

Coating: Conformal silicone-ceramic.

Core: Ceramic.

Terminals: Solder-coated copper clad axial lead.

Derating

Linearly from

100% @ +25°C to
0% @ +275°C.

Electrical

Tolerance: ±5% (J type), ±1% (F type) (other tolerances available).

Power rating: Based on 25°C free air rating (other wattages available).

Overload: Under 5 watts: 5 times rated wattage for 5 seconds. 5 watts and over: 10 times rated wattage for 5 seconds.

Temperature coefficient:

Under 1Ω: ±90 ppm/°C
1Ω to 9.99Ω: ±50 ppm/°C
10Ω and over: ±20 ppm/°C

FEATURES

- Economical
- Applications include commercial, industrial and communications equipment
- Stability under high temperature conditions
- All-welded construction
- CECC sizes available
- RoHS compliant product available Jan. 2006 Add "E" suffix to part number to specify.

STOCK PART NUMBERS FOR STANDARD RESISTANCE VALUES

Ohmic value	Wattage and Tolerance										Ohmic value	Wattage and Tolerance										Ohmic value	Wattage and Tolerance												
	1% Tolerance					5% Tolerance						1% Tolerance					5% Tolerance							1% Tolerance					5% Tolerance						
	Part No. Prefix ► Suffix ▼	41F—1	43F—3	45F—5	40F—10	41J—1	42J—2	43J—3	45J—5	40J—10		Part No. Prefix ► Suffix ▼	41F—1	43F—3	45F—5	40F—10	41J—1	42J—2	43J—3	45J—5	40J—10		Part No. Prefix ► Suffix ▼	41F—1	43F—3	45F—5	40F—10	41J—1	42J—2	43J—3	45J—5	40J—10			
0.1	R10	✓	+	+	+	+	+	+	+	+	68	68R	✓	✓	✓	✓	✓	✓	✓	+	✓	2,200	2K2	✓	✓	✓	✓	✓	✓	✓	✓				
0.15	R15	✓	✓	+	+	✓	✓	✓	✓	✓	75	75R	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	2,500	2K5	✓	✓	✓	✓	✓	✓	✓	✓			
0.2	R20	✓	+	+	+	✓	✓	✓	✓	✓	82	82R	◆	+	✓	✓	✓	✓	✓	✓	✓	✓	82	82R	◆	+	✓	✓	✓	✓	✓	✓	✓		
0.25	R25										100	100	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	100	100	✓	✓	✓	✓	✓	✓	✓	✓			
0.3	R30	✓	✓	✓	✓	✓	✓	✓	✓	✓	120	120	◆	✓	✓	✓	✓	✓	✓	✓	✓	✓	120	120	◆	✓	✓	✓	✓	✓	✓	✓			
0.33	R33										125	125	✓	◆	✓	✓	✓	✓	✓	✓	+	✓	125	125	✓	◆	✓	✓	✓	✓	✓	✓			
0.4	R40										150	150	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	150	150	✓	✓	✓	✓	✓	✓	✓	✓			
0.5	R50	✓	+	+	+	✓	✓	✓	✓	✓	180	180	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	180	180	✓	✓	✓	✓	✓	✓	✓	✓			
0.75	R75	✓	◆	✓	✓	✓	✓	✓	✓	✓	200	200	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	200	200	✓	✓	✓	✓	✓	✓	✓	✓			
1	1R0	+	✓	✓	✓	✓	✓	✓	✓	✓	220	220	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	220	220	✓	✓	✓	✓	✓	✓	✓	✓			
1.5	1R5	✓	✓	✓	✓	✓	✓	✓	✓	✓	225	225	◆	✓	✓	✓	✓	✓	✓	✓	✓	✓	225	225	◆	✓	✓	✓	✓	✓	✓	✓	✓		
2	2R0	✓	✓	✓	✓	✓	✓	✓	✓	✓	250	250	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	250	250	✓	✓	✓	✓	✓	✓	✓	✓	✓		
2.2	2R2	✓	✓	✓	✓	✓	✓	✓	✓	✓	270	270	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	270	270	✓	✓	✓	✓	✓	✓	✓	✓	✓		
3	3R0	✓	✓	✓	✓	✓	✓	✓	✓	✓	300	300	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	300	300	✓	✓	✓	✓	✓	✓	✓	✓	✓		
4	4R0	✓	✓	✓	✓	✓	✓	✓	✓	✓	330	330	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	330	330	✓	✓	✓	✓	✓	✓	✓	✓	✓		
5	5R0	✓	✓	✓	✓	✓	✓	✓	✓	✓	350	350	◆	✓	✓	✓	✓	✓	✓	✓	✓	✓	350	350	◆	✓	✓	✓	✓	✓	✓	✓	✓		
7.5	7R5	✓	✓	✓	✓	✓	✓	✓	✓	✓	390	390	◆	✓	✓	✓	✓	✓	✓	✓	✓	✓	390	390	◆	✓	✓	✓	✓	✓	✓	✓	✓		
10	10R	✓	✓	✓	✓	✓	✓	✓	✓	✓	400	400	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	400	400	✓	✓	✓	✓	✓	✓	✓	✓	✓		
12	12R	◆	✓	✓	✓	✓	✓	✓	✓	✓	450	450	◆	✓	✓	✓	✓	✓	✓	✓	✓	✓	450	450	◆	✓	✓	✓	✓	✓	✓	✓	✓		
15	15R	✓	✓	+	✓	✓	✓	✓	✓	✓	470	470	+	✓	✓	✓	✓	✓	✓	✓	✓	✓	470	470	+	✓	✓	✓	✓	✓	✓	✓	✓		
18	18R	◆	✓	✓	✓	✓	✓	✓	✓	✓	500	500	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	500	500	✓	✓	✓	✓	✓	✓	✓	✓	✓		
20	20R	✓	✓	✓	✓	✓	✓	✓	✓	✓	560	560	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	560	560	✓	✓	✓	✓	✓	✓	✓	✓	✓		
22	22R	✓	✓	✓	✓	✓	✓	✓	✓	✓	600	600	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	600	600	✓	✓	✓	✓	✓	✓	✓	✓	✓		
25	25R	✓	✓	✓	✓	✓	✓	✓	✓	✓	680	680	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	680	680	✓	✓	✓	✓	✓	✓	✓	✓	✓		
27	27R	◆	✓	✓	✓	✓	✓	✓	✓	✓	750	750	◆	✓	✓	✓	✓	✓	✓	✓	✓	✓	750	750	◆	✓	✓	✓	✓	✓	✓	✓	✓	✓	
30	30R	✓	✓	✓	✓	✓	✓	✓	✓	✓	800	800	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	800	800	✓	✓	✓	✓	✓	✓	✓	✓	✓		
33	33R	✓	✓	✓	✓	✓	✓	✓	✓	✓	820	820	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	820	820	✓	✓	✓	✓	✓	✓	✓	✓	✓		
35	35R	✓	◆	✓	✓	✓	✓	✓	✓	✓	900	900	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	900	900	✓	✓	✓	✓	✓	✓	✓	✓	✓		
39	39R	✓	✓	✓	✓	✓	✓	✓	✓	✓	1,000	1,000	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	1,000	1,000	✓	✓	✓	✓	✓	✓	✓	✓	✓		
40	40R	✓	✓	✓	✓	✓	✓	✓	✓	✓	1,100	1,100	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	1,100	1,100	✓	✓	✓	✓	✓	✓	✓	✓	✓		
47	47R	✓	✓	✓	✓	✓	✓	✓	✓	✓	1,200	1,200	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	1,200	1,200	✓	✓	✓	✓	✓	✓	✓	✓	✓		
50	50R	✓	✓	✓	✓	✓	✓	✓	✓	✓	1,500	1,500	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	1,500	1,500	✓	✓	✓	✓	✓	✓	✓	✓	✓		
56	56R	✓	✓	✓	✓	✓	✓	✓	✓	✓	1,800	1,800	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	1,800	1,800	✓	✓	✓	✓	✓	✓	✓	✓	✓		
62	62R	✓	✓	✓	✓	✓	✓	✓	✓	✓	2,000	2,000	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	2,000	2,000	✓	✓	✓	✓	✓	✓	✓	✓	✓		

◆ = Most popular stock values

✓ = Stock values

<p