HUBER+SUHNER® DATA SHEET RF & Components: 4901.17.A



Description

Resistive Power Divider, Low Power

Product Configuration

Connector (side 1) N jack (female) Connector (side 2) N jack (female) Connector (side 3) N jack (female)



Technical Data

Electrical Data

Nominal Impedance 50 Ω DC to 2 GHz Frequency Range

DC to 0.5 0.5 to 1 Frequency sub Range (GHz) 1 to 2 Ampl. Tracking max. (dB) 0.1 0.2 0.3 VSWR max. 1.05 1.07 1.15 Amplitude tracking max. (dB) 0.1 0.2 0.3 Phase tracking max. (deg)

Insertion Loss (dB)

Power Rating 1 Watt average power to 70 °C ambient temperature, linearly derated to 0 Watt at 130 °C

ambient temperature.

Isolation (dB) 6 (nominal between two ports)

Mechanical Data

Dimensions 16 / 16 / 64 (height / width / length coaxial in mm)

Weight 0.1074 kg

Environmental Data

2002/95/EC (RoHS) compliant

Material Data

Piece Part (side 1, 2, 3) Material Surface Plating

Gold Plating (without Nickel underplating) Centre contact Copper Beryllium Alloy

SUCOPLATE (R) Plating Outer contact Brass Body SUCOPLATE (R) Plating Brass

Related Documents

Outline drawing On request

Ordering Information

Single packaging 4901.17.A

Additional Information

Remarks

Insulator

Interface dimensions acc. to IEC 60169-16_MIL-STD-348A/304_CECC 22210

PFA / PTFE

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

It is exclusively in written agreements that we provide our customers with warrants and representations as to the bechnical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.

HUBER+SUHNER - Excellence in Connectivity Solutions

Document: DOC-0000178167 E Issued: 29.06.2010 11:47:12 **Uncontrolled Copy** Page 1/1



HUBER+SUHNER AG RF Industrial 9100 Herisau, Switzerland Phone +41 (0)71 353 41 11 Fax +41 (0)71 353 45 90 www.hubersuhner.com