

Target Specification

5SNG 0600R120500

1200V 600A LoPak Phase Leg IGBT Module

$V_{CE} = 1200\text{ V}$

$I_C = 600\text{ A} \times 2$


Press-fit pins for reliable auxiliary contacts

Ultra low-loss rugged Trench IGBT chipset

NTC thermistor for temperature sensing

Cu baseplate for low thermal resistance

Industry standard package



Maximum rated values

Parameter	Symbol	Conditions	min	max	units
Collector-emitter voltage	V_{ces}	$V_{GE} = 0\text{ V}, T_{vj} \geq 25\text{ °C}$		1200	V
DC collector current	I_c	$T_c = 115\text{ °C}, T_{vj} = 150\text{ °C}$		600	A
Peak collector current	I_{cm}	$t_p = 1\text{ ms}$		1200	A
Gate-emitter voltage	V_{ges}		-20	20	V
DC forward current	I_f			600	A
Peak forward current	I_{frm}	$t_p = 1\text{ ms}$		1200	A
Surge current	I_{fsm}			1600	A
IGBT short circuit SOA	t_{psc}	$t_p \leq 8\text{ }\mu\text{s}, V_{GE} \leq 15\text{ V}, V_{CC} = 800\text{ V}$ $V_{CE,max} = V_{CES} - L_{s,CE} \cdot di/dt, T_{vj} = 150\text{ °C}$		8	us
Isolation voltage	V_{isol}	1 min, $f = 50\text{ Hz}$		4000	V
Max Junction temperature	T_{vj}		-40	175	C
Junction operating temperature	$T_{vj(op)}$		-40	150	C
Case temperature	T_c		-40	125/150	C
Storage temperature	T_{stg}		-40	125	C
Mounting torques	M_s, M_{t1}	Base-heatsink, M5 screws or Main terminals, M6 screws	3	6	Nm

IGBT characteristic values

Parameter	Symbol	Conditions		min	typ	max	units
Collector-emitter breakdown voltage	V _{(BR)CES}	V _{GE} = 0 V, I _C = 10 mA, T _{vj} = 25 °C		1300			V
Collector-emitter saturation voltage	V _{CEsat}	I _C = 600A, V _{GE} = 15 V	T _{vj} =25C		1.6		V
			T _{vj} =125C		1.75		V
			T _{vj} =150C		1.9		V
Collector cut-off current	I _{CES}	V _{CE} = 1200 V, V _{GE} = -15 V	T _{vj} =25C			0.1	mA
			T _{vj} =125C		3		mA
			T _{vj} =150C		4		mA
Gate leakage current	I _{GES}	V _{CE} = 0 V, V _{GE} = ±20 V				60	nA
Gate-emitter threshold voltage	V _{GE(th)}	I _C = 12 mA, V _{CE} = V _{GE} , T _{vj} = 25 °C			5		V
Gate charge	Q _G				TBD		uC
Input capacitance	C _{ies}				TBD		nF
Internal gate resistance	R _{Gint}				0.67		Ohms
Turn-on delay time	t _{d(on)}	I _C = 600A, V _{CE} = 600V, V _{GE} = ±15 V, R _{G,on} = TBD	T _{vj} =25C		300		ns
			T _{vj} =125C		350		ns
			T _{vj} =150C		350		ns
Rise time	t _r		T _{vj} =25C	70		200	ns
			T _{vj} =125C	90		275	ns
			T _{vj} =150C	100		300	ns
Turn-off delay time	t _{d(off)}		T _{vj} =25C		400		ns
			T _{vj} =125C		475		ns
			T _{vj} =150C		500		ns
Fall time	t _f		T _{vj} =25C		190		ns
			T _{vj} =125C		200		ns
			T _{vj} =150C		200		ns
Turn-on switching energy	E _{on}	I _C = 600A, V _{CE} = 600V, V _{GE} = ±15 V, L _s = 35 nH, R _{G,on} = TBD	T _{vj} =25C	70			mJ
			T _{vj} =125C	100			mJ
			T _{vj} =150C	112		160	mJ
Turn-off switching energy	E _{off}	I _C = 600A, V _{CE} = 600V, V _{GE} = ±15 V, L _s = 35 nH	T _{vj} =25C		88		mJ
			T _{vj} =125C		112		mJ
			T _{vj} =150C		128		mJ
Short circuit current	I _{SC}	t _{pSC} ≤ 8 μs, V _{GE} = 15 V, V _{CC} = 800 V, V _{CEM CHIP} ≤ 1200 V	T _{vj} =150C		3000		A

Diode characteristic values

Parameter	Symbol	Conditions	min	typ	max	units
Forward voltage	V_f	$I_F = 600 \text{ A}$	$T_{vj}=25^\circ\text{C}$	1.6		V
			$T_{vj}=125^\circ\text{C}$			V
			$T_{vj}=150^\circ\text{C}$	1.7		V
Peak reverse recovery current	I_{rm}	$I_F = 600 \text{ A}, V_{CE} = 600 \text{ V},$ $V_{GE} = \pm 15 \text{ V},$ $L_S = 35 \text{ nH}, R_{g,on} = \text{TBD}$	$T_{vj}=25^\circ\text{C}$	644		A
			$T_{vj}=125^\circ\text{C}$			A
			$T_{vj}=150^\circ\text{C}$	694		A
Recovered charge	Q_r	$I_F = 600 \text{ A}, V_{CE} = 600 \text{ V},$ $V_{GE} = \pm 15 \text{ V},$ $L_S = 35 \text{ nH}, R_{g,on} = \text{TBD}$	$T_{vj}=25^\circ\text{C}$	70		μC
			$T_{vj}=125^\circ\text{C}$			μC
			$T_{vj}=150^\circ\text{C}$	120		μC
Reverse recovery time	t_{rr}	$I_F = 600 \text{ A}, V_{CE} = 600 \text{ V},$ $V_{GE} = \pm 15 \text{ V},$ $L_S = 35 \text{ nH}, R_{g,on} = \text{TBD}$	$T_{vj}=25^\circ\text{C}$			ns
			$T_{vj}=125^\circ\text{C}$			ns
			$T_{vj}=150^\circ\text{C}$		800	ns
Reverse recovery energy	E_{rec}	$I_F = 600 \text{ A}, V_{CE} = 600 \text{ V},$ $V_{GE} = \pm 15 \text{ V},$ $L_S = 35 \text{ nH}, R_{g,on} = \text{TBD}$	$T_{vj}=25^\circ\text{C}$	36		mJ
			$T_{vj}=125^\circ\text{C}$			mJ
			$T_{vj}=150^\circ\text{C}$	56		mJ

NTC Thermistor

Parameter	Symbol	Conditions	min	typ	max	units
Rated resistance	R_{25}	$T_c=25^\circ\text{C}$		5		K-ohms
R100	R_{100}	$T_c=100^\circ\text{C}$	468		517	ohms
B-value	$B_{25/50}$	$R_{25} = R_{25} \exp [B_{25/50}(1/T_2 - 1/(298.15\text{K}))]$		3375		K
B-value	$B_{25/100}$	$R_{25} = R_{25} \exp [B_{25/100}(1/T_2 - 1/(298.15\text{K}))]$		3433		K


Package properties

Parameter	Symbol	Conditions	min	typ	max	units
IGBT thermal resistance junction to case	$R_{th(j-c)} \text{ IGBT}$	per switch			0.048	K/W
Diode thermal resistance junction to case	$R_{th(j-c)} \text{ DIODE}$	per switch			0.087	K/W
IGBT thermal resistance case to heatsink	$R_{th(c-s)} \text{ IGBT}$	IGBT per switch, λ grease = $1\text{W/m} \times \text{K}$		0.029		K/W
Diode thermal resistance case to heatsink	$R_{th(c-s)} \text{ DIODE}$	Diode per switch, λ grease = $1\text{W/m} \times \text{K}$		0.048		K/W
Comparative tracking index	CTI					
Module stray inductance	$L_{\sigma \text{ CE}}$	per switch		20		nH
Resistance, terminal-chip	$R_{CC'+EE'}$	per switch	$T_{vj}=25^\circ\text{C}$	0.95		m-ohms
			$T_{vj}=125^\circ\text{C}$	1.35		
			$T_{vj}=150^\circ\text{C}$	1.55		

Mechanical properties

Parameter	Symbol	Conditions		min	typ	max	units
Dimensions	L x W x H	Typical		152 x 62 x 17			mm
Clearance distance in air	d _a	according to IEC 60664-1 and EN 50124-1	Term. to base:	12.5			
			Term. to term:	10			
Surface creepage distance	d _s		Term. to base:	14.5			
			Term. to term:	13			
Mass	m				350		g

Electrical configuration



Outline drawing ³⁾

Note: all dimensions are shown in millimeters




ABB Power Grids Switzerland Ltd.

A Hitachi ABB Joint Venture

Semiconductors

Fabrikstrasse 3

CH-5600 Lenzburg, Switzerland

Phone: +41 58 586 1419

Fax: +41 58 586 1306

E-Mail: abbsem@hitachi-powergrids.com

Internet: hitachiabb-powergrids.com/semiconductors

We reserve the right to make technical changes or to modify the contents of this document without prior notice.

We reserve all rights in this document and the information contained therein. Any reproduction or utilization of this document or parts thereof for commercial purposes without our prior written consent is forbidden.

Any liability for use of our products contrary to the instructions in this document is excluded.