

A2W/AH2W ATTENUATORS

2.9mm, 40 GHz, 2 Watts

SPECIFICATIONS:

Models: 2AW, 2AHW

RoHS
Compliant

AEROFLEX
A passion for performance.


Electrical:

Frequency Range _____ DC – 40 GHz
Standard dB Values _____ 3, 6, 10, 20, 30dB
Attenuation Accuracy: _____ DC – 26.5 GHz 26.5 – 40 GHz
3 & 6 dB _____ ± 0.5 dB _____ ± 0.8 dB
10, 20 & 30 dB _____ ± 0.6 dB _____ ± 1.0 dB
VSWR:
DC – 18 GHz _____ 1.30:1 Max.
18 – 40 GHz _____ 1.40:1 Max.
Input Power _____ 2 Watts Avg @ 25° C
DERATED LINEARLY TO 0.1 WATTS @ +125°C
Impedance _____ 50 Ohms
Operating Temp Range _____ -65°C to +125°C

Mechanical:


2.9mm Connectors _____ Passivated Stainless Steel
(Mate both Mechanically & Electrically with
all SMA, K* & 3.5mm Series Connectors.)
Conductors _____ Gold Plated Beryllium Copper

* K is a Trademark of Anritsu Corp.



AH STYLE

5/16 [7.9] Hex



A STYLE

HOW TO ORDER:

Style
A = A Style (No Hex)
AH = AH Style (Hex)
Model Number: **40AY2W-XX**
dB Value

Ordering Examples:
Model Number: **40A2W-20**
DC – 40 GHz; 20 dB; Style

Note: Dimensions in Brackets are Expressed in Millimeters and are for Reference Only.
Design specifications are subject to change without notice.
Contact factory for technical specifications before purchasing or use.

5105: REV B

AEROFLEX
INMET

Aeroflex / Inmet, Inc. • 300 Dino Drive, Ann Arbor, MI 48103 • U.S.A.
888-244-6638 or 734-426-5553 • FAX: 734-426-5557
www.aeroflex-inmet.com • inmet-sales@eroflex.com