

Data Sheet

Microwave Cable Assemblies

PMASF526E/11PC35/11PC35/36in Part No.: 85207926

Main characteristics

SUCOFLEX 526E microwave cable assemblies set a new measurement standard through 26.5 GHz. Absolute time delay matched +/- 1ps.



Product configuration

Cable Type	SUCOFLEX 526E		
Length	914.0 mm 36.0 in REF to REF		
	Type	Series	
Connector A	SF_11_PC35-510	3.5mm	straight plug
Connector B	SF_11_PC35-510	3.5mm	straight plug

Technical data

Electrical data

Impedance	50.0 Ω
Operating Frequency max	26.5 GHz
Min. Return Loss	19.0 dB up to 18 GHz
	16.6 dB up to 26.5 GHz
Max. Insertion Loss	1.64 dB
Signal Delay	4.3 ns/m
Propagation Velocity	77.0 %
Screen Effectiveness	≥ 90.0 dB up to 18.0 GHz
Amplitude Stability vs. Flexure	+/- 0.1 dB
Phase Stability vs. Flexure	+/- 8°

Mechanical data

Cable Diameter	5.5 mm
Minimum Bending Radius Static	16.0 mm

Environmental data

Operation Temperature Range	-40.0 °C ... 85.0 °C
-----------------------------	----------------------

Additional information

Marketing Information	Absolute time delay matched +/- 1ps
-----------------------	-------------------------------------