

COAXIAL CONNECTOR, PC 1.0, 50 Ohm, Straight PCB jack (female)

82_PC1-S50-0-200/199_N

Properties

- Fast and easy installation
- Precision testing up to 110 GHz
- Reusable design



Product configuration		
Interface type	Gender	Standard
PC 1	jack	IEEE STD 287

Interface and material data		
Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Body	Stainless Steel	Passivated (Plating)
Insulator	PEI (Polyether-imide)	

Electrical data	
Impedance	50 Ω
Interface frequency	110 GHz

Electrical Data (frequency related)		
Frequency range	Return loss	VSWR
0 GHz ... 110 GHz	15 dB	1.43

Mechanical data	
Weight	0.0014 kg
Mating cycles	500

Environmental data	
Operation temperature	-40 °C ... 165 °C

COAXIAL CONNECTOR, PC 1.0, 50 Ohm, Straight PCB jack (female)
82_PC1-S50-0-200/199_N

Ordering Information Table	
Item number	Item description
85221628	82_PC1-S50-0-200/199_NE

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P41028 / Date of publication: 30.11.2023 / uncontrolled copy