


COAXIAL CONNECTOR, SMA, 50 Ohm, Edge mount PCB jack (female)
92_SMA-S50-0-200/122_N

Properties

- Fast and easy installation
- Precision testing up to 26.5 GHz
- Reusable design
- Mechanical intermateable with PC 3.5 (3.5 mm standard) and SK (2.92 mm standard)



Product configuration		
Interface type	Gender	Standard
SMA	jack	MIL-STD-348B

Interface and material data		
Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Body	Brass	Nickel Plating
Insulator	PEI (Polyether-imide)	

Electrical data	
Impedance	50 Ω
Interface frequency	26.5 GHz

Electrical Data (frequency related)		
Frequency range	Return loss	VSWR
0 GHz ... 26.5 GHz	17 dB	1.33

Mechanical data	
Weight	0.004 kg
Mating cycles	500
Board mounting type	edge mount

Environmental data	
Operation temperature	-40 °C ... 165 °C

COAXIAL CONNECTOR, SMA, 50 Ohm, Edge mount PCB jack (female)

92_SMA-S50-0-200/122_N

Ordering Information Table

Item number	Item description
85221629	92_SMA-S50-0-200/122_NE

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P40299 / Date of publication: 30.11.2023 / uncontrolled copy