



This document is the property of REGAL BELLOTT CORPORATION ("RBC") including its subsidiaries and divisions and contains proprietary information of RBC. This document is loaned on the express condition that neither it nor the information contained therein shall be disclosed to others without the express written consent of RBC. The information contained herein shall be returned to us as soon as requested by RBC. This document shall be returned to us upon request. This document may be subject to certain restrictions under U.S. export control laws and regulations.

97F5054

REV	SHEET
1	1

REV.	DESCRIPTION	DATE	APPROVED
1	Modified per ECN NO. 0627.	11/11/05	HV




BLADE DETAILS

SCALE 8.000

"GEM-III Capacitors are manufactured with High Grade Metallized Polypropylene Film"

Main Capacitance	: 30.00μF ±6%
Secondary Capacitance	: NIL
Volts	:370AC
Leakage Current	:30μA Max.
Frequency	:50/60 HZ
Operating Temperature	:-40 DEG C TO 70 DEG C
Storage Temperature	:-40 DEG C TO 90 DEG C
Operative Life	:60,000 HRS WITH 94% SURVIVAL
Dissipation Factor	:0.1% MAX.
Case Material	:ALUMINIUM
Cover Material	:TERNPLATE
Terminals	: 0.250"x0.031" Quick Connect Blades
Dielectric Fluid	:DIELEKTROL VI
Internal Protection	: UL RECOGNIZED PRESSURE SENSITIVE INTERRUPTER



FOR ADDITIONAL INFO REFER TO:		SIGNATURES	DATE
APPLIED PRACTICES		MODEL	RAGHU. P. H 05/22/2018
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES		DETAIL	RAGHU. P. H 05/22/2018
TOLERANCE ON:		CHECKED	RAGHU. P. H 05/26/2018
1 PL DECIMALS ± 0.1		ENGAGE	- -
2 PL DECIMALS ± 0.01		MFG	- -
3 PL DECIMALS ± 0.001		QUALITY	- -
ANGLES ± 0.5		ISSUED	- -
FRACTIONS ±			
FINISH			
MATERIAL		SOLID MODEL: CAPACITOR.ASSEMBLY	

**REGAL-BELOIT CORPORATION**

GEM III CAPACITOR OUTLINE DRAWING

8	TITLE
---	-------

SIZE	C
------	---

WING

97F5054

REV	1
-----	---

SCALE: 1.250

REF. No:

SHEET 1 OF 1