




REVISION HISTORY					
REV	DATE	ORIGINATOR	APPROVED	DCRN	CAD
A		P8172			JJ

OPERATIONAL REQUIREMENTS	
FREQUENCY RANGE:	2 - 18 GHz
VSWR (MAX):	1.35:1
INSERTION LOSS (dB MAX):	1.79
TEMPERATURE RANGE:	-55° to +150° C
IMPEDANCE:	50 Ω NOM.
VELOCITY:	74.4% NOM.

MARKING REQUIREMENTS:

MARKING TO BE 11 pt CHARACTERS IN CONTRASTING COLOR ON ITEM 3. SEE FIGURE FOR MARKER TEXT.

YY = LAST 2 DIGITS OF PRODUCTION YEAR
JJJJ = LAST 4 DIGITS OF PRODUCTION ORDER
XXX = UNIQUE SERIALIZATION NUMBER

NOTES:

- SOLDER & WORKMANSHIP IAW IPC/WHMA-A-620.
- SMA CONNECTOR INTERFACE IAW MIL-STD-348, FIG. 310-1.
- ASSEMBLY IS REACH/ROHS COMPLIANT.

5	Sn96	HIGH TEMP LEAD FREE SOLDER	AR
4	200-0003-007	MARKERS, Ø3/8", POLYOLEFIN, 3:1, BLACK	6"
3	200-0001-007	STRAIN RELIEF, Ø3/8", RNF-100, 2:1, BLACK	4"
2	50-340P	CONNECTOR, SMA-SP	2
1	421-010	CABLE, TRUE BLUE 205	47.375"
ITEM	PART NUMBER	DESCRIPTION	QTY

BILL of MATERIAL			
ENGINEER: Jacob Joslin	PROJECT No: 8172	 10221 WERCH DRIVE Woodridge, IL 60517 www.teledynestorm.com	TITLE: TRUE BLUE 205 CABLE ASSEMBLY
QUALITY:			
UNLESS OTHERWISE SPECIFIED: DIM .XX ± .13" DIM .XXX ± .063" ANGLES ± 3° ALL DIMENSIONS ARE IN INCHES.		DRAWING SIZE: B	SCALE: N/A
		SHEET 1 of 1	
		DRAWING NUMBER: ROHS-90-010-048	REVISION LEVEL: A

USE AND DISCLOSURE OF DATA
Information contained herein is classified as EAR99 under the U.S. Export Administration Regulations. Export, re-export or diversion contrary to U.S. law is prohibited.

PROPRIETARY INFORMATION:
This document contains proprietary information and, except with permission from Teledyne Storm Microwave, such information shall not be published or disclosed for any purpose and the document shall not be copied whole or in part. © 2024 TELEDYNE STORM MICROWAVE