



This document is the property of REGAL BELOIT CORPORATION ("RBC") including its subsidiaries and divisions and contains proprietary information of RBC. It is loaned to you for your use only on the condition that you will not disseminate the information contained herein to any third party without the express written consent of RBC, and that the information shall be used by the recipient only as approved expressly by RBC. This document shall be returned to RBC upon its request. This document may be subject to certain restrictions under U.S. export control laws and regulations.



Main Capacitance	: 25.00μF ±6%
Secondary Capacitance	: NIL
Volts	:600AC
Leakage Current	:30μA Max.
Frequency	:50/60 HZ
Operating Temperature	: -40 DEG C TO 70 DEG C
Storage Temperature	: -40 DEG C TO 90 DEG C
Operative Life	:60,000 HRS WITH 94% SURVIVAL
Dissipation Factor	:0.1% MAX.
Case Material	:ALUMINIUM
Cover Material	:TERNPLATE
Terminals	: 0.250"x0.031" Quick Connect Blades
Dielectric Fluid	:DIELEKTROL VI
Internal Protection	: UL RECOGNIZED PRESSURE SENSITIVE INTERRUPTER



FOR ADDITIONAL INFO REFER TO:		SIGNATURES		DATE		 REGAL-BELOTT CORPORATION	
APPLIC PRACTICES		MODEL	RAGHU. P.H	05/14/03			
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES		DETAIL	RAGHU. P.H	05/14/03			
TOLERANCE ON:		CHECKED	RAGHU. P.H	05/21/03			
1 PL DECIMALS ± 0.1		ENGRG	-				
2 PL DECIMALS ± 0.01		MFG	-			GEM III CAPACITOR OUTLINE DRAWING	
3 PL DECIMALS ± 0.001		QUALITY	-				
ANGLES ± 0.5		ISSUED	-				
FRACTIONS ±							
FINISH							
		SOLID MODEL: 21CAPACITOR.ASM		SIZE	DRAWING	REV	
				C		97F8254	I
MATERIAL				SCALE: 1.250		REF. No: .	
						SHEET 1 OF 1	