






This document is the property of REGAL DELOIT CORPORATION ("RDC") including its subsidiaries and divisions and contains proprietary information of RDC. This document is loaned on the express condition that neither it nor the information contained herein shall be disclosed to others without the express written consent of RDC. If the document is damaged or lost, the borrower must notify RDC immediately. The document and its contents are to be returned only as approved expressly by RDC. This document shall be returned to RDC upon request. This document may be subject to certain restrictions under U.S. export control laws and regulations.

REVISIONS			
REV.	DESCRIPTION	DATE	APPROVED
1	Modified as per ECN No. 0627	11/11/05	HV
2	Modified as per ECN No. 0668 & 0673	7/18/08	HV



SCALE 1.500

SPECIFICATIONS:

"GEM-III Capacitors are manufactured with High Grade Metallized Polypropylene Film"

Main Capacitance	: 7.50μF ±6%
Secondary Capacitance	: NIL
Volts	:370AC
Leakage Current	:30μA Max.
Frequency	:50/60 HZ
Operating Temperature	:-40 DEG C TO 70 DEG C
Storage Temperature	:-40 DEG C TO 90 DEG C
Operative Life	:60,000 HRS WITH 94% SURVIVAL
Dissipation Factor	:0.1% MAX.
Case Material	:ALUMINIUM
Cover Material	:STEEL TIN PLATED
Terminals	: 0.250"x0.031" Quick Connect Blades
Dielectric Fluid	:DIELEKTROL VI
Internal Protection	: UL RECOGNIZED PSI A10000AFC

FOR ADDITIONAL INFO REFER TO:	SIGNATURES	DATE
APPLIED PRACTICES	MODEL	NPS 07/25/01
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	DETAIL	NPS 07/25/01
TOLERANCE ON:	CHECKED	HV 07/25/01
1 PL DECIMALS $\pm$ 0.1	ENGRG	-
2 PL DECIMALS $\pm$ 0.01	MFG	-
3 PL DECIMALS $\pm$ 0.001	QUALITY	-
ANGLES $\pm$ 0.5	ISSUED	-
FRACTIONS $\pm$		
FINISH		
MATERIAL	SOLID MODEL: 2TCAPACITOR.ASM	

**REGAL-BELOIT CORPORATION**

0	TITLE
---	-------

GEM III CAPACITOR OUTLINE DRAWING

SIZE	DRAWING	REV
C	97F9001	2
SCALE: 1:250	REF. No:	SHEET 1 OF 1

