

## Coaxial Cable Connector 25\_716-50-7-2/003\_-

### Description

Straight panel cable jack, flange mount

Interface standards

IEC 61169-4\_CECC 22190\_DIN 47223\_VG 95250

### Technical Data

#### Electrical Data

Impedance 50  $\Omega$   
Interface frequency max. 7.5 GHz

#### Mechanical Data

Centre contact crimped  
Outer 2contact crimped  
Weight 0.1113 kg

#### Environmental Data

Operating temperature -65 °C to 165 °C  
2011/65/EU (RoHS) compliant

#### Material Data

Piece Parts	Material	Surface Plating
Centre contact	Bronze / Brass	Silver Plating
Outer contact	Bronze	Silver Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Gasket	NR (Natural Rubber)	
Crimp ferrule	Brass	

### Related Documents

Outline drawing DOU-00008825  
Catalogue drawing DCA-00008827  
Assembly instruction DOC-0000179881  
Mounting hole DOU-00008824

### Ordering Information

Single package 25\_716-50-7-2/003\_-E  
Bulk 100 pcs package 25\_716-50-7-2/003\_-H

### Additional Information

Suitable cables RG\_214\_/U, GX\_07272\_D