

SPECIFICATIONS		CABLE GROUPS
ELECTRICAL SPECIFICATIONS IMPEDANCE: 75 Ω WORKING VOLTAGE RATING: 500 VRMS FREQUENCY RANGE: 0-1 GHz MECHANICAL SPECIFICATIONS MATING: 3/8 - 32 THREAD CABLING: CRIMP PLATING G - GOLD N - NICKEL T - TIN DIELECTRIC MATERIAL PE - POLYETHYLENE PP - POLYPROPYLENE	GRP	FOR THESE CABLE TYPES
	D	RG-59, 59A, 59B, 62, 62A, 62C/U; ALPHA 9059, 9062, 9830, 9840, 9845; BELDEN 7807A, 8221, 8241, 9169, 9204, 9228; CANARE LV-61S; COMMScope 5555, 5560, 5563; HARBOUR HPF200
	Q	RG-6/U TYPE; BELDEN 1694A, 9248; COMMScope 5715, 5729, 5765



PHOTOS FOR REFERENCE ONLY, SHOWN AT 100% ACTUAL SIZE.

PART #	FIG	DESCRIPTION	CBL GRP	NOTES	PLATING			RECOMMENDED TOOL
					BDY	P/C	DIE	
RFF-1401-D	1	MALE COMPRESSION CRIMP PLUG		BLACK BAND, FOR RG-59/U	N	T	PE	RFA-4004-20
RFF-1401-Q	1	MALE COMPRESSION CRIMP PLUG		RED BAND, FOR RG-6/U	N	T	PE	RFA-4004-20
RFF-1401-Q3	1	MALE COMPRESSION CRIMP PLUG		BLUE BAND, FOR RG-6/U QUAD	N	T	PE	RFA-4004-20
RFF-1402-08	2	MALE CRIMP	Q	NO PIN, WITH GASKET & SILICON, FOR RG-6/U	--	--	PE	RFA-4005-306
RFF-1402-D	3	MALE CRIMP	D	FOR RG-59/U	N	N	PE	RFA-4005-306
RFF-1442	4	FEMALE RIGHT ANGLE PCB MOUNT		4 LEG, LONG	N	T	PE	
RFF-1442-03	4	FEMALE RIGHT ANGLE PCB MOUNT		4 LEG, LONG	N	T	PP	
RFF-1442-1	4	FEMALE RIGHT ANGLE PCB MOUNT		4 LEG, SHORT	N	T	PP	
RFF-1444	5	FEMALE BULKHEAD		WITH HEX FLANGE & SOLDER TAB	N	T	PP	
RFF-1445-5	6	ADAPTER		F MALE QUICK DISCONNECT TO F FEMALE	N	T	PE	
RFF-1445-5-1	6	ADAPTER		F MALE QUICK DISCONNECT TO F FEMALE	G	G	PE	
RFF-1446-10	7	RIGHT ANGLE ADAPTER		F MALE TO F FEMALE	N	N	PE	
RFF-1448	8	ADAPTER		F MALE TO F MALE	N	N	PE	
RFF-1450-03	9	FEMALE VERTICAL PCB MOUNT		4 LEG, .32" ON CENTER, TAB CONTACT	N	T	PE	
RFF-1476	10	ADAPTER		F FEMALE TO F FEMALE	N	T	PE	
RFF-1476-1	10	ADAPTER		F FEMALE TO F FEMALE	G	T	PE	
RFF-1477	11	BULKHEAD ADAPTER		F FEMALE TO F FEMALE	N	T	PE	