



PLUG



LETTER	INCHES [MILLIMETERS]	
	MINIMUM	MAXIMUM
A	.019 [0.48]	.021 [0.53]
B	.079 [2.00]	.082 [2.07]
C	.144 [3.66]	.148 [3.76]
D	.000	.012 [0.30]
E	.111 [2.81]	.126 [3.20]
F	.164 [4.16]	-
G	.111 [2.81]	.126 [3.20]

JACK



LETTER	INCHES [MILLIMETERS]	
	MINIMUM	MAXIMUM
A	.071 [1.80]	.078 [1.97]
B	.135 [3.43]	.137 [3.48]
C	.142 [3.61]	.148 [3.75]
D	.091 [2.31]	.110 [2.79]
E	.103 [2.61]	.110 [2.79]
F	.158 [4.00]	.162 [4.12]
G	.030 [0.75]	.033 [0.85]

NOTE 1: I.D. TO MEET VSWR AND CONTACT RESISTANCE WHEN MATED WITH .019/.021 DIA. PIN

SPECIFICATIONS

ELECTRICAL SPECIFICATIONS

IMPEDANCE: 50 Ω
WORKING VOLTAGE RATING: 335 VRMS
FREQUENCY RANGE: 0-6 GHz

MECHANICAL SPECIFICATIONS

MATING: SNAP ON COUPLING
INTERFACE: CECC 22220
CABLING: CRIMP

PLATING

N - NICKEL
G - GOLD

DIELECTRIC MATERIAL

T - TEFLON

GRP

FOR THESE CABLE TYPES

B	TIMES LMR-100A; RG-174, 188, 188A, 316/U; ALPHA 9174, 9316; BELDEN 7805A, 8216, 83269, 83284, 84316; COMMScope AMC-174, WBC-100
B1	RG-316/U DOUBLE SHIELD; RD-316; BELDEN 83269; COLEMAN 1596
C	TIMES LMR-195; RG-58, 58A, 58C, 141, 141A/U; ANDREW CNT-195, CNT-195-DB, CNT-195-FR; BELDEN 7806A, 8219, 8240, 8259, 8262, 9201, 9203, 9310, 9311; COMMScope WBC-195, WBC-195R, 0268, TCOM-195, TCOM-195-FR; HARBOUR HPF195



FIG. 1
RMX-8000-1B, -1C, -B, -B1



FIG. 2
RMX-8000-1B-LCK



FIG. 3
RMX-8010-1B,
-1B1, -1C, -B, -B1



FIG. 4
RMX-8010-1B-LCK



FIG. 5
RMX-8100-B



FIG. 6
RMX-8252-1B



FIG. 7
RMX-8300, -1



FIG. 8
RMX-8350, -1



FIG. 9
RMX-8400-1

PHOTOS FOR REFERENCE ONLY, SHOWN AT 150% ACTUAL SIZE.

PART #	FIG	DESCRIPTION	CBL GRP	NOTES	PLATING			RECOMMENDED TOOL
					BDY	P/C	DIE	
RMX-8000-1B	1	CRIMP PLUG	B	FOR RG-174/U	G	G	T	RFA-4009-204
RMX-8000-1B-LCK	2	CRIMP PLUG	B	FOR RG-174/U	G	G	T	RFA-4009-204
RMX-8000-1C	1	CRIMP PLUG	C	FOR RG-58/U	G	G	T	RFA-4009-206
RMX-8000-B	1	CRIMP PLUG	B	FOR RG-174/U	N	G	T	RFA-4009-204
RMX-8000-B1	1	CRIMP PLUG	B1	FOR RG-316/U DOUBLE SHIELD	N	G	T	RFA-4009-204
RMX-8010-1B	3	RIGHT ANGLE CRIMP PLUG	B	FOR RG-174/U	G	G	T	RFA-4009-204
RMX-8010-1B-LCK	4	RIGHT ANGLE CRIMP PLUG	B	FOR RG-174/U	G	G	T	RFA-4009-204
RMX-8010-1B1	3	RIGHT ANGLE CRIMP PLUG	B1	FOR RG-316/U DOUBLE SHIELD	G	G	T	RFA-4009-204
RMX-8010-1C	3	RIGHT ANGLE CRIMP PLUG	C	FOR RG-58/U	G	G	T	RFA-4009-206
RMX-8010-B	3	RIGHT ANGLE CRIMP PLUG	B	FOR RG-174/U	N	G	T	RFA-4009-204
RMX-8010-B1	3	RIGHT ANGLE CRIMP PLUG	B1	FOR RG-316/U DOUBLE SHIELD	N	G	T	RFA-4009-204
RMX-8100-B	5	CRIMP JACK	B	FOR RG-174/U	N	G	T	RFA-4009-204
RMX-8252-1B	6	BULKHEAD CRIMP JACK	B	FOR RG-174/U	G	G	T	RFA-4009-204
RMX-8300	7	RIGHT ANGLE JACK PCB MOUNT			N	G	T	
RMX-8300-1	7	RIGHT ANGLE JACK PCB MOUNT			G	G	T	
RMX-8350	8	VERTICAL JACK PCB MOUNT			N	G	T	
RMX-8350-1	8	VERTICAL JACK PCB MOUNT			G	G	T	
RMX-8400-1	9	RIGHT ANGLE PCB MOUNT			G	G	T	