




LOC	DIST	REVISIONS				
		P	LTR	DESCRIPTION	DATE	DWN
GP	00		C	REVISED PER ECO-08-014902	10-NOV-08	ZMRCWR

D




TERMINATED VIEW

C



A



1 MOLDED PARTS: UL RATED 94V-0 THERMOPLASTIC, BLACK.

2 CONTACTS: PHOSPHOR BRONZE PER QQ-B-750.

3 CONTACTS: PLATED WITH .000030 MIN GOLD IN LOCALIZED GOLD PLATE AREA, .000050 MIN TIN ON TERMINATION END, ALL OVER .000050 MIN NICKEL ON ENTIRE CONTACT.
OR
GOLD FLASH OVER PALLADIUM-NICKEL PLATE .000030 MIN TOTAL IN LOCALIZED GOLD PLATE AREA, .000050 MIN TIN ON TERMENATION END, ALL OVER .000050 MIN NICKEL ON ENTIRE CONTACT.

4 POLARIZING FEATURE DOES NOT EXIST ON SAME END AS THE POSN #1 INDICATOR ON 10 AND 14 POSN PRODUCT.



D

C

1658623

B

A



3.100	3.380	3.150	63	64	1-1658623-2
2.900	3.180	2.950	59	60	1-1658623-1
2.400	2.680	2.450	49	50	1-1658623-0
1.900	2.180	1.950	39	40	1658623-9
1.600	1.880	1.650	33	34	1658623-8
1.400	1.680	1.450	29	30	1658623-7
1.200	1.480	1.250	25	26	1658623-6
1.100	1.380	1.150	23	24	1658623-5
.900	1.180	.950	19	20	1658623-4
.700	.980	.750	15	16	1658623-3
.600	.880	.650	13	14	1658623-2
.400	.680	.450	9	10	1658623-1
D	C	B	A	NO OF POSN	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN R. SAMICK 25AUG03	 Tyco Electronics Corporation Harrisburg, PA 17105-3608				
DIMENSIONS: INCHES		CHK C. ROHDE 25AUG03					
	TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ± - 1 PLC ± - 2 PLC ± - 3 PLC ± .005 4 PLC ± - ANGLES ± 5°	APVD M. WALMSLEY 25AUG03	NAME RECEPTACLE ASSY, MILITARY POLARIZATION, LEAD FREE, AMP-LATCH™ NOVO				
		PRODUCT SPEC 108-40000					
		APPLICATION SPEC 114-40005	SIZE A2	CAGE CODE 00779	DRAWING NO C-1658623	RESTRICTED TO	
		MATERIAL SEE NOTES	FINISH SEE NOTES	WEIGHT -			
		CUSTOMER DRAWING			SCALE 4:1	SHEET 1 of 1	REV C