

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

-,-

© COPYRIGHT - BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.

LOC

DIST

REVISIONS

AF

50

P

LTR

DESCRIPTION

DATE

DWN

APVD

K





REVISED PER ECR-06-009299

29AUG06

HMR

RL

- 1 TAB DIMENSIONS $.032^{+.001}_{-.002} \times .250$
- 2 WIRE STRIP LENGTH .281
- 3 INSULATION SIZE .160 MAX DIA
- 4 CONTINUOUS STRIP ON REELS
- 5 DIMENSION DOES NOT INCLUDE TRIM BURR
- 6 .015 MAX CARRIER TRIM BURR PER SIDE IS ALLOWABLE IN THE SHADED AREA



HOUSING: NYLON, COLOR-BLUE TRANSLUCENT
TAB: #3 HARD BRASS, TIN .000080 MIN

3-520106-2

MATERIAL & FINISH

PART NO

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN P FORTNEY 11/15/88

CHK MS FEHER 11/30/88

APVD KA RANDOLPH 12/14/88

PRODUCT SPEC

108-2017

APPLICATION SPEC

114-2123

WEIGHT -

CUSTOMER DRAWING

tyco
ElectronicsTyco Electronics Corporation
Harrisburg, PA 17105-3608NAME
TAB ASSEMBLY, ULTRA-FAST,
.250 SERIES, 16-14 AWG

SIZE CAGE CODE DRAWING NO RESTRICTED TO

A3 00779 C-520106 -

SCALE 4:1 SHEET 1 OF 1 REV K