

DATASHEET

N(F) to N(F) Bulk Head Adapter

Product Name

1. NFBH-NF-002





N(F) to N(F) Bulk Head Adapter

Document No.	CRD-DS-2251-08
Date / Rev.	25.May.2023 / 1
Confidential level	N/A

1. Product

1-1. N(F) to N(F) Bulk Head Adapter

(P/N : NFBH-NF-002)

2. Specifications

2-1. Material

Body : Brass, 3Mat'l

Center Conductor : BeCu, Au Plated

Insulator : PTFE

2-2. Environmental

Operating Temperature : -50°C to 150°C

2-3. Electrical

Impedance : 50Ω Typ.

Operating Freq. : DC to 12.4GHz

VSWR : 1.15 : 1 @12.4GHz Typ.

1.20 : 1 @12.4GHz Max.

Insertion Loss : -0.06dB x $\sqrt{f}$

RF Leakage : -100dB




Document No.	CRD-DS-2251-08
Date / Rev.	25.May.2023 / 1
Confidential level	N/A

3. Drawing

3-1. N(F) to N(F) Bulk Head Adapter

(P/N : NFBH-NF-002)





Document No.	CRD-DS-2251-08
Date / Rev.	25.May.2023 / 1
Confidential level	N/A

4. Data

4-1. N(F) to N(F) Bulk Head Adapter

(P/N : NFBH-NF-002)

