


## P/N: NFST-11F8G-NFST-3ft

Unit: mm



[ Label A ] Product Name SENSORVIEW / SV YY.MM.DD-XXX

Product Configurat	ion	
Connector A	N Type	Female / Straight
Connector B	N Type	Female / Straight
Raw Cable	11F8G	
Length	3ft (36 inch)	0.914m

Electrical & Mechanical	Specification	
Characteristic Impedance	50Ω Typ.	
Operating Frequency	DC to 8GHz	
VSWR	1.20 @8GHz Typ.	1.30 @8GHz Max.
Insertion Loss	-1.15dB @8GHz Typ.	-1.25dB @8GHz Min.
Velocity of Propagation	77% nominal	
Shielding Effectiveness	≤ -80dB @8GHz	
Outer Diameter (Cable)	4.9mm ±0.1 (0.192 inch)	
Minimum Bend Radius	25mm (0.98 inch)	
Phase Stability vs. Flexure	Max. 2° @8GHz	
Loss Stability vs. Flexure	△ 0.05dB to 8GHz	

Environmental Specification		
Temperature Range	-40°C ~ +125°C	
RoHs	Compliant	

Option		
Phase Matched (Relative)	±1ps @8GHz	

SensorView is certified according to ISO 9001, ISO 14001, AS/EN9100.

The information herein are for reference only and do not represent any warranty.