P/N	CABLE TYPE	(Ø A)
−1	Ø .141 SEMI−RIGID	.143 MIN.
−1SF	Ø .141 SEMI−RIGID	.143 MIN.
−1NP	Ø .141 SEMI−RIGID	.143 MIN.
−2	Ø .085 SEMI−RIGID	.088 MIN.
−2SF	Ø .085 SEMI−RIGID	.088 MIN.
−2NP	Ø .085 SEMI−RIGID	.088 MIN.
−3	Ø .141 MICROPOROUS	.143 MIN.
−3SF	Ø .141 MICROPOROUS	.143 MIN.
−3NP	Ø .141 MICROPOROUS	.143 MIN.

REVISIONS				
ZONE	REV.	DESCRIPTION(S)	DATE	BY
−	A	ECO 19233	04.18.06	DKN



DRAWING NO.	REV.
5286	A

* ALL ITEMS TO BE PACKAGED AND SHIPPED UNASSEMBLED.

MATERIAL:

Body:
303 sst per ASTM A−582.
Center Conductor:
BeCu alloy per ASTM B−196.
Dielectric:
PTFE per ASTM D−1710.

ELECTRICAL:

Impedance: 50 Ohms nominal.
Frequency Range: DC to 18.0 GHz.
VSWR: 1.05 + .008*f(GHz).
Insertion Loss: .05 $\sqrt{f}$(GHz).
Working Voltage: 500 Vrms max @ sea level.
Dielectric Withstanding Voltage: 1500 Vrms min.
R.F. HiPot Voltage: 1000 Vrms min @ 5MHz.
Corona Level: 375 Vrms @ 70,000 ft.
Insulation Resistance: 5000 MegOhms min.
R.F. Leakage: −(90 − fGHz) dB
Contact Resistance:
Center Contact: 3.0 Milliohm max.
Outer Contact: 2.0 Milliohm max.

MECHANICAL:

Mating Characteristics:
Interface per Mil−Std−348.
Force To Engage & Disengage:
Torque: 2 inch−lbs max.
Connector Durability:
500 cycles min @ 12 cycles/minute max.
Permeability: Less than 2.0 mu.

ENVIRONMENTAL:

Temperature Range: −65°C to +165°C.
Thermal Shock:
Mil−Std−202, Method 107, Test Cond. B.
Moisture Resistance:
Mil−Std−202, Method 106, Insulation resistance at least 200 MegOhms within 5 minutes after removal from humidity.
Corrosion:
Mil−Std−202, Method 101, Test Cond. B.
Vibration:
Mil−Std−202, Method 204, Test Cond. D.
Shock:
Mil−Std−202, Method 213, Test Cond. I.

FINISH:

Center Conductor:
Gold plate per ASTM B−488, over nickel under plate per AMS−QQ−N−290.
Body:
For (basic): Gold plate per ASTM B−488, over nickel under plate per AMS−QQ−N−290.
For (SF's): Passivate per ASTM A−967.
For (NP's): Nickel plate per AMS−QQ−N−290.

APPLICABLE TENSOLITE DOCUMENTS

WORK STD	PROD INST	ASSY INST
NA	NA	NA

NOTICE

THIS DRAWING EMBODIES A CONFIDENTIAL PROPRIETARY DESIGN ORIGINATED BY TENSOLITE COMPANY AND ALL DESIGN, MANUFACTURING REPRODUCTION, USE AND SALE RIGHTS REGARDING THE SAME ARE EXPRESSLY RESERVED. IT IS SUBMITTED UNDER A CONFIDENTIAL RELATIONSHIP FOR A SPECIFIED PURPOSE AND THE RECIPIENT AGREES BY ACCEPTING THIS DRAWING NOT TO SUPPLY OR DISCLOSE ANY INFORMATION REGARDING IT TO ANY UNAUTHORIZED PERSON TO INCORPORATE IN OTHER PROJECTS ANY SPECIAL FEATURES PECULIAR TO THIS DESIGN. ALL PATENT RIGHTS HERETO ARE EXPRESSLY RESERVED BY TENSOLITE COMPANY, LONG BEACH, CALIFORNIA 90815.

TOLERANCES AND NOTES EXCEPT AS NOTED

DIMENSIONS ARE IN INCHES.
LINEAR .XX ±.015 .XXX ±.005 ANGULAR ± 1/2°
FRACTION ± 1/32

1. MACHINE FINISH: 63 √ RMS
2. BREAK ALL SHARP EDGES .003 MAX.
3. MACHINED FILLETS .005 MAX.
4. MACHINED SURFACES SQUARE TO RESPECTIVE AXIS WITHIN .005 INCHES PER INCH.
5. MACHINED DIAMETERS CONCENTRIC WITHIN .002 T.I.R.
6. DIMENSIONS TO BE MET BEFORE PLATING.
7. CHAMFER ALL THREADS 45°.
8. THREADS PER H−28
9. REMOVE FRAYED EDGES ON TEFLON.
10. REMOVE ALL BURRS.

MATERIAL	SIZE	SPECIFICATION	PROCUREMENT
−	−	−	−

NEXT ASSY

APPROVAL INITIALS		DATE
DRAWN BY	IMG	03.13.02
CHECKED	DNg	04.19.06
QUALITY		
ENGINEERING	ATV	04.19.06

Tensolite
HIGH PERFORMANCE CABLES & INTERCONNECT SYSTEMS
Long Beach, California 90815

TITLE: SMA FEMALE STRAIGHT TO SEMI−RIGID CABLE

SCALE: 5:1 | SUB−DIRECTORY\FILENAME: OL_\ | SHEET 1 OF 1

SIZE	CAGE CODE	DRAWING NO.	REV.
C	30990	5286	A