

1595 MHz GPS Patch Antenna




Key Features:

Center Frequency:	1595 MHz (+/-5 MHz)
Gain:	5.5 dBi (min)
Reliability:	MTBF=1×10 ⁶ /pc.hr
Package Size:	36 x 36 x 6.5 mm


Electrical Specifications¹: (at +25°C)

Testing Item	Test Constraints	Min	Nom	Max	Unit
Center Frequency (Fo)	with 70x70 mm ground plane		1595		MHz
Frequency Bandwidth (BW)	Return loss ≤ -10dB	44			MHz
VSWR	at center frequency			1.5:1	
Gain (Zenith)	with 70x70 mm ground plane	5.5			dBi
Axial Ratio	(0 ~ 90°)			4.5	dB
Polarization			RHCP		
Impedance			50		ohms
Frequency Temperature Coefficient			0±10		ppm/°C
Operating Temperature range		-40		+85	°C
Storage Temperature range		-40		+100	°C

Outline Drawing (in mm)



Characteristic curve



Ordering Information

Part Number	RANP1595C
-------------	-----------

¹ Specifications subject to change without notice

Richardson RFPD, Inc.

40W267 Keslinger Road

P.O. Box 307

LaFox, IL 60147

Telephone: (800) 737-6937

(630) 208-2700

Fax: (630) 208-2662

Internet: www.richardsonrfpd.com**IMPORTANT NOTICE**

RICHARDSON RFPD, INC. AND ITS AFFILIATES RESERVE THE RIGHT TO MAKE CHANGES TO THE PRODUCT(S) OR INFORMATION CONTAINED HEREIN WITHOUT NOTICE. RICHARDSON RFPD, INC. ASSUMES NO RESPONSIBILITY FOR ANY ERRORS WHICH MAY APPEAR IN THIS DOCUMENT.

WARRANTY INFORMATION APPLICABLE TO THE PRODUCT IDENTIFIED HEREIN IS AVAILABLE UPON REQUEST. NOTHING CONTAINED HEREIN SHALL CONSTITUTE A WARRANTY, REPRESENTATION OR GUARANTEE OF ANY KIND. RICHARDSON RFPD, INC. EXPRESSLY DISCLAIMS ALL OTHER WARRANTIES, EXPRESS AND/OR IMPLIED INCLUDING BUT NOT LIMITED TO WARRANTIES OF MERCHANTABILITY, AND OF FITNESS FOR A PARTICULAR PURPOSE, USE OR APPLICATION.

NO PART OF THIS DOCUMENT MAY BE COPIED OR REPRODUCED IN ANY FORM OR BY ANY MEANS WITHOUT THE PRIOR WRITTEN CONSENT OF RICHARDSON RFPD, INC.

WARNING

RICHARDSON RFPD, INC. PRODUCTS ARE NOT INTENDED FOR USE IN LIFE SUPPORT APPLIANCES, DEVICES OR SYSTEMS. USE OF A RICHARDSON RFPD, INC. PRODUCT IN ANY SUCH APPLICATION WITHOUT WRITTEN CONSENT IS PROHIBITED.