


1 ~ 150 MHz Low Noise Power Amplifier¹



RPAC0001A is a low noise, wideband, and high linearity amplifier module with an unconditionally stable design. The amplifier offers 17.4 dB typical gain, 2.70 dB noise figure, +30 dBm P_{1dB} and +48 dBm output IP₃ over the frequency range from 1 MHz to 150 MHz. With the active components being hermetically sealed, it can be configured to operate over a range of -55C to +85C. The unit is housed with SMA connectors and built-in DC block capacitors.



It is designed to meet the rugged standards of MIL-STD-202.

Key Features:

Wide Frequency Range: 1 ~ 150 MHz
 High Gain: 17.4 dB
 Low Noise Figure: 2.7 dB
 High P_{1dB}: 30.5 dBm
 High OIP₃: 48 dBm
 Impedance: 50 Ohm
 Single DC Supply: 210 mA @ +10V
 Connectors: SMA Female
 MTBF²: > 1,000,000 hrs
 Built-In Functions: DC blocks at input and output ports, temperature compensation circuitry

Absolute Maximum Ratings³:

Parameters	Symbol	Value	Units
DC Power Supply Voltage	V _{dd}	12	V
Drain Current	I _{dd}	250	mA
Total Power Dissipation	P _{diss}	3	W
RF Input Power	P _{In,Max}	20	dBm
Channel Temperature	T _{ch}	150	°C
Storage Temperature	T _{STG}	-55 ~ +85	°C
Maximum Operating Temperature	T _{O,MAX}	-40 ~ +85	°C
Thermal Resistance	R _{th,jc}	TBD	°C/W

Electrical Specifications: (at room temperature)

Testing Item	Symbol	Test Constraints	Min	Nom	Max	Unit
Gain	S ₂₁	1 ~ 150 MHz	17.2	17.4	17.6	dB
Gain Variation	ΔG	1 ~ 150 MHz		+/- 0.2		dB
Input Return Loss	S ₁₁	1 ~ 150 MHz	10	12		dB
Output Return Loss	S ₂₂	1 ~ 150 MHz	14	15		dB
Reverse Isolation	S ₁₂	1 ~ 150 MHz	25			dB
Noise Figure	NF	1 ~ 150 MHz		2.7		dB
Output Power @ 1dB Gain Comp. Point	P _{1dB}	1 ~ 150 MHz	29	30.5		dBm
Output IP ₃	OIP ₃	2-Tone, Pout 0 dBm each, 1 MHz separation	46	48		dBm
Current Consumption	I _{dd}	V _{dd} = +10 V		210		mA
Power Supply Voltage	V _{dd}		+8 ⁴	+10	+12	V
Operating Temperature	T _o	Case temperature	-40		+85	°C

¹ Specifications are subject to change without notice.

² MTBF: Mean Time Between Failure, per TR-NWT-000332, ISSUE 3, September, 1990, T=40°C

³ Operation of this device above any one of these parameters may cause permanent damage.

⁴ The lower DC supply voltage reduces the performance.

Available exclusively from Richardson RFPD - 800-737-6937 (U.S. & Canada) - 630-208-2700 (International)

Or visit www.richardsonrfpd.com. See important product notice on last page of this document.

Internal Richardson Document #	Origination Date: November 2007	Rev: V2 Date: April 2011	Page 1/5
--------------------------------	------------------------------------	-----------------------------	----------

Frequency Response




FIG. 1 Small signal performance.




FIG. 2 P_{1dB} and OIP3 at room temperature.




FIG. 3 Noise figure performance at full temperature




FIG. 4 Stability factor k




FIG. 5 Frequency response in extended frequency




FIG. 6 Outline of package

Ordering Information

Part Number	RPAC0001A
-------------	-----------

Small Signal S-Parameters:

! RPAC0001A, 9/5/03
 ! Vd = +10.0V, Id = 200 mA
 # Mhz s ma r 50

0.1	0.290	-16.0	7.521	-172.0	0.040	15.7	0.150	-174.5
10	0.270	-3.9	7.460	178.2	0.040	0.4	0.170	-178.2
20	0.270	-6.9	7.440	176.2	0.040	-0.8	0.170	-177.3
30	0.280	-10.5	7.430	174.4	0.040	-0.8	0.170	-176.5
40	0.280	-13.9	7.420	172.6	0.040	-1.8	0.170	-175.3
50	0.280	-17.0	7.410	170.8	0.040	-1.7	0.170	-174.5
60	0.280	-20.6	7.390	169.0	0.040	-2.7	0.170	-173.6
70	0.280	-23.9	7.360	167.2	0.041	-2.3	0.170	-172.5
80	0.280	-26.9	7.350	165.3	0.040	-3.3	0.180	-171.7
90	0.280	-30.3	7.320	163.6	0.040	-3.3	0.180	-170.5
100	0.290	-33.8	7.310	161.9	0.040	-2.9	0.180	-169.5
110	0.290	-37.0	7.280	160.1	0.040	-3.9	0.190	-169.5
120	0.290	-40.1	7.260	158.4	0.040	-4.0	0.190	-169.1
130	0.290	-43.3	7.240	156.6	0.040	-4.5	0.190	-169.0
140	0.290	-46.5	7.220	154.8	0.040	-5.4	0.200	-168.6
150	0.300	-49.7	7.190	153.0	0.041	-6.2	0.200	-168.2
160	0.300	-52.6	7.150	151.2	0.040	-5.9	0.210	-167.3
170	0.300	-55.9	7.110	149.4	0.040	-6.3	0.210	-167.2
180	0.310	-58.5	7.070	147.7	0.041	-6.8	0.220	-167.2
190	0.310	-61.4	7.030	146.0	0.041	-7.6	0.220	-166.5
200	0.310	-63.8	6.981	144.2	0.041	-8.9	0.230	-166.5
210	0.320	-66.4	6.940	142.5	0.041	-8.2	0.240	-166.5
220	0.320	-68.9	6.890	140.7	0.041	-8.3	0.240	-166.8
230	0.330	-71.4	6.821	139.0	0.040	-8.9	0.250	-167.4
240	0.330	-74.2	6.750	137.6	0.040	-9.4	0.260	-168.8
250	0.340	-77.1	6.720	136.0	0.040	-10.2	0.260	-169.5
260	0.340	-79.4	6.680	134.0	0.040	-10.9	0.260	-169.6
270	0.340	-81.6	6.611	132.1	0.041	-11.0	0.280	-169.9
280	0.350	-83.9	6.491	130.3	0.040	-11.8	0.290	-171.4
290	0.360	-86.1	6.331	129.1	0.040	-12.1	0.300	-174.2
300	0.370	-89.1	6.250	128.8	0.040	-11.4	0.300	-177.4
310	0.380	-92.7	6.289	128.3	0.040	-11.4	0.280	-179.1
320	0.380	-95.7	6.359	126.9	0.041	-12.2	0.280	-177.8
330	0.380	-98.2	6.380	124.9	0.041	-11.7	0.280	-176.4
340	0.380	-100.2	6.370	122.9	0.040	-12.3	0.290	-175.9
350	0.380	-102.4	6.320	121.0	0.041	-12.8	0.290	-175.7
360	0.380	-104.1	6.261	119.1	0.042	-13.5	0.300	-175.8
370	0.390	-105.8	6.191	117.2	0.041	-14.8	0.310	-176.8
380	0.390	-107.6	6.081	115.6	0.041	-14.8	0.320	-178.5
390	0.400	-109.5	5.961	114.3	0.041	-15.8	0.330	179.1
400	0.410	-112.0	5.880	113.8	0.041	-15.2	0.330	176.6
410	0.420	-114.9	5.890	112.9	0.041	-14.7	0.320	175.5
420	0.420	-117.3	5.930	111.5	0.042	-15.0	0.320	176.0
430	0.420	-119.3	5.930	109.7	0.042	-16.3	0.320	176.7
440	0.420	-121.3	5.900	107.8	0.042	-17.2	0.330	176.9
450	0.420	-123.0	5.860	105.9	0.043	-19.6	0.340	176.6
460	0.430	-124.7	5.810	104.1	0.043	-19.3	0.350	176.1
470	0.430	-126.4	5.740	102.5	0.042	-20.6	0.350	175.2
480	0.430	-128.2	5.670	101.0	0.043	-20.6	0.360	174.3
490	0.440	-130.1	5.610	99.6	0.043	-20.7	0.360	173.5
500	0.440	-132.0	5.570	98.1	0.043	-22.2	0.370	173.0

Richardson RFPD, Inc.

40W267 Keslinger Road

P.O. Box 307

LaFox, IL 60147

Telephone: (800) 737-6937

(630) 208-2700

Fax: (630) 208-2662

Internet: www.richardsonrfpd.com**IMPORTANT NOTICE**

RICHARDSON RFPD, INC. AND ITS AFFILIATES RESERVE THE RIGHT TO MAKE CHANGES TO THE PRODUCT(S) OR INFORMATION CONTAINED HEREIN WITHOUT NOTICE. RICHARDSON RFPD, INC. ASSUMES NO RESPONSIBILITY FOR ANY ERRORS WHICH MAY APPEAR IN THIS DOCUMENT.

WARRANTY INFORMATION APPLICABLE TO THE PRODUCT IDENTIFIED HEREIN IS AVAILABLE UPON REQUEST. NOTHING CONTAINED HEREIN SHALL CONSTITUTE A WARRANTY, REPRESENTATION OR GUARANTEE OF ANY KIND. RICHARDSON RFPD, INC. EXPRESSLY DISCLAIMS ALL OTHER WARRANTIES, EXPRESS AND/OR IMPLIED INCLUDING BUT NOT LIMITED TO WARRANTIES OF MERCHANTABILITY, AND OF FITNESS FOR A PARTICULAR PURPOSE, USE OR APPLICATION.

NO PART OF THIS DOCUMENT MAY BE COPIED OR REPRODUCED IN ANY FORM OR BY ANY MEANS WITHOUT THE PRIOR WRITTEN CONSENT OF RICHARDSON RFPD, INC.

WARNING

RICHARDSON RFPD, INC. PRODUCTS ARE NOT INTENDED FOR USE IN LIFE SUPPORT APPLIANCES, DEVICES OR SYSTEMS. USE OF A RICHARDSON RFPD, INC. PRODUCT IN ANY SUCH APPLICATION WITHOUT WRITTEN CONSENT IS PROHIBITED.

Available exclusively from Richardson RFPD - 800-737-6937 (U.S. & Canada) - 630-208-2700 (International)

Or visit www.richardsonrfpd.com. See important product notice on last page of this document.

Internal Richardson Document #	Origination Date: November 2007	Rev: V2 Date: April 2011	Page 5/5
--------------------------------	------------------------------------	-----------------------------	----------