

DATASHEET

SMA(F) to SMA(F) 4Hole Adapter

Product Name

1. SMAF4H-SMAF-001





SMA(F) to SMA(F) 4Hole Adapter

Document No.	CRD-DS-2250-04
Date / Rev.	25.May.2023 / 1
Confidential level	N/A

1. Product

1-1. SMA(F) to SMA(F) 4Hole Adapter

(P/N : SMAF4H-SMAF-001)

2. Specifications

2-1. Material

Body : Brass, Au Plated

Center Conductor : BeCu, Au Plated

Insulator : PTFE

2-2. Environmental

Operating Temperature : -50°C to 150°C

2-3. Electrical

Impedance : 50Ω Typ.

Operating Freq. : DC to 18GHz

VSWR : 1.15 : 1 @18GHz Typ.

1.25 : 1 @18GHz Max.

Insertion Loss : -0.05dB x $\sqrt{f}$

RF Leakage : -100dB



3. Drawing

3-1. SMA(F) to SMA(F) 4Hole Adapter

(P/N : SMAF4H-SMAF-001)





SMA(F) to SMA(F) 4Hole Adapter

Document No.	CRD-DS-2250-04
Date / Rev.	25.May.2023 / 1
Confidential level	N/A

4. Data

4-1. SMA(F) to SMA(F) 4Hole Adapter

(P/N : SMAF4H-SMAF-001)

