


P/N : SMAFST-11A8GD-SMAFST-3ft

Unit : mm



[Label A]
Product Name
SENSORVIEW / SV YY.MM.DD-XXX

Product Configuration

Connector A	SMA	Female / Straight
Connector B	SMA	Female / Straight
Raw Cable	11A8GD	
Length	3ft (36 inch)	0.914m

Electrical & Mechanical Specification

Characteristic Impedance	50Ω Typ.	
Operating Frequency	DC to 8GHz	
VSWR	1.15 @8GHz Typ.	1.20 @8GHz Max.
Insertion Loss	-1.15dB @8GHz Typ.	-1.25dB @8GHz Min.
Velocity of Propagation	77% nominal	
Shielding Effectiveness	≤ -80dB @8GHz	
Outer Diameter (Cable)	5.8mm ±0.1 (0.228 inch)	
Minimum Bend Radius	25mm (0.98 inch)	
Phase Stability vs. Flexure	Max. 5° @8GHz	
Loss Stability vs. Flexure	△ 0.05dB to 8GHz	

Environmental Specification

Temperature Range	-40°C ~ +135°C
RoHs	Compliant

Option

Phase Matched (Relative)	±1ps @8GHz
--------------------------	------------

SensorView is certified according to ISO 9001, ISO 14001, AS/EN9100.

The information herein are for reference only and do not represent any warranty.