Technical Data Sheet

TestPro4.2S Nm Nm

PAGE 1/1	ISSUE 25/04/19	SERIES TestPro	PART NUMBER TP4.2S-N-MM-XX

CUSTOMER : All SPECIFICATION : - ISSUE : - DATE -

All dimensions are in mm



Part Number	Overall Length (mm)	Tolerance (mm)
TP4.2S-N-MM-24	610	±12
TP4.2S-N-MM-36	914	±18
TP4.2S-N-MM-48	1220	±24
TP4.2S-N-MM-78	2000	±40

CONNECTORS DESIGNATION

Connector 1: **R163064151**
N straight plug
Stainless steel passivated
Torque wrench : 170 N.cm

Connector 2: **R163064151**
N straight plug
Stainless steel passivated
Torque wrench : 170 N.cm

CABLE DESIGNATION **TestPro4.2S**
PROTECTIVE JACKET **-**
OUTER DIAMETER **4,90** mm max
MARKING **White marking on a black sliding heatshrink sleeve**

ELECTRICAL CHARACTERISTICS

Characteristic impedance **50 ±2** Ohms

Frequency band : **DC-18** GHz

Part Number	Length (mm)	Max insertion loss (dB) at 20°C	Max VSWR at 20°C
TP4.2S-N-MM-24	610	1,92	1,30 : 1
TP4.2S-N-MM-36	914	2,72	1,30 : 1
TP4.2S-N-MM-48	1220	3,52	1,30 : 1
TP4.2S-N-MM-78	2000	5,57	1,30 : 1

Phase stability with bending (*) **<3,06** ° **at 18GHz**
Stabilité de phase en enroulement

Attenuation stability with bending (*) **<0.05** dB **at 18GHz**
Stabilité de pertes en enroulement

(*) Test done according to IEC60966-1. Cable is submitted to 5 windings 360° clockwise on a 100mm mandrel. Measurement is done after 5 windings.

MECHANICAL CHARACTERISTICS

Static bending radius : **25** mm

Dynamic bending radius : **50** mm

Life (Connectors) : **5 000** Cycles

ENVIRONMENTAL CHARACTERISTICS

Temperature range : **-55°C to +105°C**

This document contains proprietary information and such information shall not be disclosed to any third party for any purpose whatsoever or used for manufacturing purposes without prior written agreement from Radiall. The data defined in this document are given as an indication, in the effort to improve our products; we reserve the right to make any changes judged necessary.