

LC SIMPLEX PC SINGLEMODE ADAPTOR
 METALLIC ALIGNMENT SLEEVE

Packaging
 100


Series
 LC

Issue
 03 24 04

Page
 1 / 2

Adaptor : color BLUE

Simplex



Original dimensions in mm [inch]

**LC SIMPLEX PC SINGLEMODE ADAPTOR
METALLIC ALIGNMENT SLEEVE**
Packaging
100

Series
LC

Issue
03 24 04

Page
2 / 2

Adaptor : color BLUE

Simplex

GENERAL

- ☐ **TYPE**

IEC 61754-20 (LC)
 RJ-45 latching system
 Receptacle color : BLUE
- ☐ **MOUNTING**

Snap-in mounting
 Max. panel thickness 1.7 mm
- ☐ **ALIGNMENT SLEEVE**

Metallic

CHARACTERISTICS (Depending on fibre or cable construction)

- ☐ **MATERIAL**

Plastic molded : Material in accordance with TELCORDIA GR-326 CORE
 Inflammability V0 (UL 94)
- ☐ **MECHANICAL**

Durability	200 cycles
Plug Retention	68 N
- ☐ **ENVIRONMENTAL**

Storage temperature range	-40 °C to +85 °C
Operating temperature range	-40 °C to +70 °C
- ☐ **PROOF TEST**

Straight pull	68 N
Side pull	23 N
- ☐ **VIBRATION TEST**

10 to 55 Hz, 1,5 mm (peak to peak), 2 Hr/axis

(Performance and specification : see document GEN - F727 001)