

COAXIAL CONNECTOR, MCX, 50 Ohm, Straight bulkhead receptacle, jack (female)

22_MCX-50-0-2/133_N

Properties

- Small size
- Easy to connect and disconnect
- Wide range of board connectors and cable connectors available



Product configuration

Interface type	Gender	Standard
MCX	jack	IEC 60169-36_CEEC 22220

Interface and material data

Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer conductor	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Fastening nut	Brass	SUCOPLATE (R) Plating
Washer	Bronze	SUCOPLATE (R) Plating

Electrical data

Impedance	50 Ω
Interface frequency	6 GHz

Mechanical data

Weight	0.0008 kg
Mating cycles	500
Flange type	round flange / dia. 6.5
Tab style	Special

Environmental data

Operation temperature	-65 °C ... 165 °C
-----------------------	-------------------

COAXIAL CONNECTOR, MCX, 50 Ohm, Straight bulkhead receptacle, jack (female)
22_MCX-50-0-2/133_N

Ordering Information Table		
Item number	Item description	Packaging type
22644433	22_MCX-50-0-2/133_NH	Bulk 100 pcs

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P2804 / Date of publication: 26.11.2023 / uncontrolled copy