

COAXIAL ADAPTER, PC 1.85, 50 Ohm, jack / jack (female / female)

31_PC185-50-0-1/199_NE

Properties

- Precision interfaces
- Excellent electrical performance
- Premium base materials and platings



Product configuration		
Interface type	Gender	Standard
PC 1.85	jack (female)	IEC 60169-32
PC 1.85	jack (female)	IEC 60169-32

Interface and material data		
PC 1.85		
Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	SUCOPRO / Gold Plating
Outer conductor	Stainless Steel	Passivated (Plating)
Body	Stainless Steel	Passivated (Plating)
Insulator	LCP (Liquid crystal polymer)	
PC 1.85		
Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	SUCOPRO / Gold Plating
Outer conductor	Stainless Steel	Passivated (Plating)
Body	Stainless Steel	Passivated (Plating)
Insulator	LCP (Liquid crystal polymer)	

Electrical data	
Impedance	50 Ω
Interface frequency	67 GHz

Electrical Data (frequency related)		
Frequency range	Return loss	VSWR
0 GHz ... 15 GHz	30 dB	1.065
15 GHz ... 25 GHz	25 dB	1.119
25 GHz ... 67 GHz	20 dB	1.222

COAXIAL ADAPTER, PC 1.85, 50 Ohm, jack / jack (female / female)
31_PC185-50-0-1/199_NE

Mechanical data		
Weight	0.011 kg	
Mating cycles	500	
Environmental data		
Operation temperature	-55 °C ... 155 °C	
Ordering Information Table		
Item number	Item description	Packaging type
84132746	31_PC185-50-0-1/199_NE	Single

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/ EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P2381 / Date of publication: 27.05.2024 / uncontrolled copy