

COAXIAL ADAPTER, QMA, 50 Ohm, jack / jack (female / female)

31_QMA-50-0-1/199_N

Properties

- Precision interfaces
- Excellent electrical performance
- Premium base materials and platings



Product configuration		
Interface type	Gender	Standard
QMA	jack (female)	QMA QLF compliant
QMA	jack (female)	QMA QLF compliant

Interface and material data		
QMA		
Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	SUCOPRO Plating
Outer conductor	Stainless Steel	
Body	Stainless Steel	
Insulator	Air Dielectric - Bead - PS	
QMA		
Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	SUCOPRO Plating
Outer conductor	Stainless Steel	
Insulator	Air Dielectric - Bead - PS	

Electrical data	
Impedance	50 Ω
Interface frequency	18 GHz

Electrical Data (frequency related)		
Frequency range	Return loss	VSWR
0 GHz ... 1.5 GHz	35 dB	1.036
1.5 GHz ... 6 GHz	30 dB	1.065

COAXIAL ADAPTER, QMA, 50 Ohm, jack / jack (female / female)
31_QMA-50-0-1/199_N

Mechanical data		
Weight	0.0035 kg	
Mating cycles	500	
Environmental data		
Operation temperature	-60 °C ... 100 °C	
Ordering Information Table		
Item number	Item description	Packaging type
23023171	31_QMA-50-0-1/199_NE	Single

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/ EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P2374 / Date of publication: 27.05.2024 / uncontrolled copy