

COAXIAL ADAPTER, 4.1/9.5 - N, 50 Ohm, plug / jack (male / female)

33_4195-N-50-1/---_U

Properties

- Precision interfaces
- Excellent electrical performance
- Premium base materials and platings



Product configuration		
Interface type	Gender	Standard
4.1/9.5	plug (male)	IEC 60169-11_DIN 47231_VG 95277
N-precision	jack (female)	IEC 60169-16_MIL-STD-348A/402_CECC 22210

Interface and material data		
4.1/9.5		
Piece parts	Material	Plating
Centre contact	Brass	Gold Plating (without Nickel underplating)
Outer conductor	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating
N-precision		
Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (without Nickel underplating)
Outer conductor	Stainless Steel	
Body	Stainless Steel	
Insulator	PFA / PTFE	

Electrical data	
Impedance	50 Ω
Interface frequency	14 GHz

Electrical Data (frequency related)		
Frequency range	Return loss	VSWR
0 GHz ... 6 GHz	32 dB	1.05

COAXIAL ADAPTER, 4.1/9.5 - N, 50 Ohm, plug / jack (male / female)
33_4195-N-50-1/---_U

Electrical Data (frequency related)		
Frequency range	Return loss	VSWR
6 GHz ... 14 GHz	24 dB	1.12
Mechanical data		
Weight	0.0481 kg	
Mating cycles	500	
Environmental data		
Operation temperature	-40 °C ... 85 °C	
Ordering Information Table		
Item number	Item description	Packaging type
22646154	33_4195-N-50-1/---_UE	Single

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/ EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P2274 / Date of publication: 27.05.2024 / uncontrolled copy