

COAXIAL ADAPTER, N-precision - TNC, 50 Ohm, plug / jack (male / female)

33_N-TNC-50-51/1--_U

Properties

- Precision interfaces
- Excellent electrical performance
- Premium base materials and platings



Product configuration		
Interface type	Gender	Standard
N-precision	plug (male)	IEC 60169-16_MIL-STD-348A/402_CECC 22210
TNC-precision	jack (female)	IEC 60169-17_MIL-STD-348A/406_CECC 22200

Interface and material data		
N-precision		
Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (without Nickel underplating)
Outer conductor	Stainless Steel	Passivated (Plating)
Body	Stainless Steel	Passivated (Plating)
Insulator	Air Dielectric - Bead - PPH	
Coupling nut	Brass	SUCOPLATE (R) Plating
TNC-precision		
Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (without Nickel underplating)
Outer conductor	Stainless Steel	Passivated (Plating)
Body	Stainless Steel	
Insulator	Air Dielectric - Bead - PPH	

Electrical data	
Impedance	50 Ω
Interface frequency	11 GHz
VSWR	DC - 12.4 GHz ($\leq 1.05 + 0.01 f \text{ GHz}$)

COAXIAL ADAPTER, N-precision - TNC, 50 Ohm, plug / jack (male / female)
33_N-TNC-50-51/1--_U

Mechanical data		
Weight		0.0446 kg
Mating cycles		500
Environmental data		
Operation temperature		-55 °C ... 70 °C
Ordering Information Table		
Item number	Item description	Packaging type
22543955	33_N-TNC-50-51/1--_UE	Single
Additional Information		
Remarks		Operating specification acc. IEEE Std 287: temperature 13 °C to 33 °C

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/ EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P2188 / Date of publication: 27.05.2024 / uncontrolled copy