

COAXIAL ADAPTER, QN - N, 50 Ohm, plug / jack (male / female)

33_QN-N-50-1/133_N

Properties

- Wide range of different configurations
- Most common interfaces available
- Accurate transitions
- Effective and reliable interconnection solutions
- Appropriate materials

**Product configuration**

Interface type	Gender	Standard
QN	plug (male)	QN QLF compliant
N	jack (female)	IEC 61169-16_MIL-STD-348A/304_CECC 22210

Interface and material data

QN		
Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	SUCOPRO Plating
Outer conductor	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating
Gasket	EPDM (Ethylene propylene diene rubber)	
N		
Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	SUCOPRO Plating
Outer conductor	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	

Electrical data

Impedance	50 Ω
Interface frequency	11 GHz

Mechanical data

Weight	0.0289 kg
Mating cycles	500

COAXIAL ADAPTER, QN - N, 50 Ohm, plug / jack (male / female)
33_QN-N-50-1/133_N

Environmental data		
Operation temperature		-40 °C ... 125 °C
Ordering Information Table		
Item number	Item description	Packaging type
23036033	33_QN-N-50-1/133_NE	Single
Additional Information		
Remarks	typical return loss / VSWR: up to 1 GHz min. 40 dB / 1.02 up to 2.5 GHz min. 34 dB / 1.04 up to 11 GHz min. 23 dB / 1.15	

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/ EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P2167 / Date of publication: 27.05.2024 / uncontrolled copy