

COAXIAL ADAPTER, SMA - MCX, 50 Ohm, plug / jack (male / female)

33_SMA-MCX-50-1/111_N

Properties

- Wide range of different configurations
- Most common interfaces available
- Accurate transitions
- Effective and reliable interconnection solutions
- Appropriate materials



Product configuration		
Interface type	Gender	Standard
SMA	plug (male)	IEC 60169-15_MIL-STD-348A/310_CEEC 22110
MCX	jack (female)	IEC 60169-36_CEEC 22220

Interface and material data		
SMA		
Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (without Nickel underplating)
Outer conductor	Copper Beryllium Alloy	Gold Plating (without Nickel underplating)
Body	Brass	Gold Plating (without Nickel underplating)
Insulator	PFA / PTFE	
Coupling nut	Bronze	Gold Plating (Nickel underplated)
Gasket	VMQ (Silicone rubber)	
MCX		
Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Body		Gold Plating (without Nickel underplating)
Insulator	PFA / PTFE	

Electrical data	
Impedance	50 Ω
Interface frequency	6 GHz
VSWR	DC - 6 GHz ($\leq 1.03 + 0.03 f \text{ GHz}$)

Mechanical data	
Weight	0.0062 kg
Mating cycles	500

COAXIAL ADAPTER, SMA - MCX, 50 Ohm, plug / jack (male / female)
33_SMA-MCX-50-1/111_N

Environmental data	
Operation temperature	-65 °C ... 125 °C

Ordering Information Table		
Item number	Item description	Packaging type
22645488	33_SMA-MCX-50-1/111_NE	Single

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/ EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P2158 / Date of publication: 12.04.2024 / uncontrolled copy