

COAXIAL ADAPTER, SMA, 50 Ohm, Bulkhead, jack / jack (female / female)

34_SMA-50-0-3/111_N

Properties

- Wide range of different configurations
- Most common interfaces available
- Accurate transitions
- Effective and reliable interconnection solutions
- Appropriate materials



Product configuration

Interface type	Gender	Standard
SMA	jack (female)	IEC 60169-15_MIL-STD-348A/310_CECC 22110
SMA	jack (female)	IEC 60169-15_MIL-STD-348A/310_CECC 22110

Interface and material data

SMA		
Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer conductor	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Body	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Insulator	PFA / PTFE	
Gasket	FKM (Fluoro elastomer, FPM)	
Fastening nut	Brass	Gold Plating (Nickel underplated)
Washer	Bronze	Gold Plating (Nickel underplated)
SMA		
Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer conductor	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Body	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Insulator	PFA / PTFE	
Gasket	FKM (Fluoro elastomer, FPM)	
Fastening nut	Brass	Gold Plating (Nickel underplated)
Washer	Bronze	Gold Plating (Nickel underplated)

Electrical data

Impedance	50 Ω
Interface frequency	18 GHz

COAXIAL ADAPTER, SMA, 50 Ohm, Bulkhead, jack / jack (female / female)
34_SMA-50-0-3/111_N

Electrical Data (frequency related)		
Frequency range	Return loss	VSWR
0 GHz ... 3 GHz	26 dB	1.1
3 GHz ... 7 GHz	20 dB	1.2
7 GHz ... 18 GHz	17 dB	1.3
Mechanical data		
Weight	0.0068 kg	
Mating cycles	500	
Environmental data		
Operation temperature	-20 °C ... 165 °C	
Ingress protection (IP Rating)	Mated / IP68	
Ordering Information Table		
Item number	Item description	Packaging type
22641297	34_SMA-50-0-3/111_NE	Single
Additional Information		
Remarks	Hermetically sealed: leak rate <= 10^-7 Torr l/s (atm cc/s) O-ring mount bulkhead feedthrough design, leak rate dependent on environmental condition, typ. <= 10^-6 Torr l/s"	

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/ EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P2086 / Date of publication: 27.05.2024 / uncontrolled copy