


COAXIAL ADAPTER, MMBX, 50 Ohm, Bulkhead, plug / plug (male / male)

35_MMBX-50-0-1/111_N

Properties

- Smallest board-to-board distance
- Very high frequencies
- Excellent return loss values
- Blind mateable
- Reliable and secure connection



Product configuration		
Interface type	Gender	Standard
MMBX	plug (male)	HUBER+SUHNER-MMBX
MMBX	plug (male)	HUBER+SUHNER-MMBX

Interface and material data		
MMBX		
Piece parts	Material	Plating
Centre contact	Copper Beryllium / Brass	SUCOPRO Plating
Outer conductor	Bronze	SUCOPRO Plating
Body	Brass	SUCOPRO Plating
Insulator	PFA / LCP	
Fastening nut	Brass	SUCOPRO Plating
Washer	Bronze	SUCOPRO Plating
MMBX		
Piece parts	Material	Plating
Centre contact	Copper Beryllium / Brass	SUCOPRO Plating
Outer conductor	Bronze	SUCOPRO Plating
Body	Brass	SUCOPRO Plating
Insulator	PFA / LCP	

Electrical data	
Impedance	50 Ω
Interface frequency	12.4 GHz

Electrical Data (frequency related)		
Frequency range	Return loss	VSWR
0 GHz ... 2.5 GHz	22 dB	1.173
2.5 GHz ... 6 GHz	18 dB	1.288

COAXIAL ADAPTER, MMBX, 50 Ohm, Bulkhead, plug / plug (male / male)
35_MMBX-50-0-1/111_N

Electrical Data (frequency related)		
Frequency range	Return loss	VSWR
6 GHz ... 12.4 GHz	16 dB	1.377
Mechanical data		
Weight	0.0032 kg	
Mating cycles	100	
Environmental data		
Operation temperature	-55 °C ... 155 °C	
Ordering Information Table		
Item number	Item description	Packaging type
23007587	35_MMBX-50-0-1/111_NE	Single

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/ EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P1937 / Date of publication: 27.05.2024 / uncontrolled copy