

COAXIAL ADAPTER, BMA - SMA, 50 Ohm, Bulkhead, plug / jack (male / female)

36_BMA-SMA-50-1/199_U

Properties

- Wide range of different configurations
- Most common interfaces available
- Accurate transitions
- Effective and reliable interconnection solutions
- Appropriate materials



Product configuration

Interface type	Gender	Standard
BMA	plug (male)	IEC 60169-33_MIL-STD-348A/321
SMA	jack (female)	IEC 60169-15_MIL-STD-348A/310_CECC 22110

Interface and material data

BMA		
Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (without Nickel underplating)
Outer conductor	Stainless Steel	
Body	Stainless Steel	
Insulator	PFA / PTFE	
Coupling nut	Stainless Steel	
Gasket	NR (Natural Rubber)	
Fastening nut	Stainless Steel	
Washer	Bronze	SUCOPLATE (R) Plating
SMA		
Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (without Nickel underplating)
Outer conductor	Stainless Steel	
Body	Stainless Steel	
Insulator	PFA / PTFE	

Electrical data

Impedance	50 Ω
Interface frequency	18 GHz
VSWR	DC - 18 GHz ($\leq 1.03 + 0.015 f \text{ GHz}$)

COAXIAL ADAPTER, BMA - SMA, 50 Ohm, Bulkhead, plug / jack (male / female)
36_BMA-SMA-50-1/199_U

Mechanical data		
Weight	0.0034 kg	
Mating cycles	500	
Environmental data		
Operation temperature	-65 °C ... 125 °C	
Ordering Information Table		
Item number	Item description	Packaging type
22645651	36_BMA-SMA-50-1/199_UE	Single

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/ EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P1936 / Date of publication: 27.05.2024 / uncontrolled copy