

COAXIAL CONNECTOR, MMPX, 50 Ohm, Straight PCB jack with ground pin in-hole and SMT Signal pin (female)

96_MMPX-50-0-2/111_N

Properties

- Excellent electrical performance at smallest dimensions
- Broadband electrical characteristics
- Mechanically very robust
- Fits a wide range of cable types



Product configuration

Gender	Standard
jack	HUBER+SUHNER MMPX STD (Patent US 7.294.023)

Interface and material data

Piece parts	Material	Plating
Centre contact	Copper Beryllium / Brass	SUCOPRO Plating
Outer conductor	Copper Beryllium Alloy	SUCOPRO Plating
Body	Brass	SUCOPRO Plating
Insulator	PTFE (Polytetrafluoroethylene)	

Electrical data

Impedance	50 Ω
Interface frequency	67 GHz

Electrical Data (frequency related)

Frequency range	Return loss	VSWR
0 GHz ... 26.5 GHz	25 dB	1.12
26.5 GHz ... 50 GHz	15 dB	1.43
50 GHz ... 67 GHz	10 dB	1.92

Mechanical data

Weight	0.0004 kg
Mating cycles	100
Board mounting type	pin-in-hole / SMT
Number of printlegs	4
Height above PCB HA	5.47 mm
Height of stand off HS	0.37 mm

COAXIAL CONNECTOR, MMPX, 50 Ohm, Straight PCB jack with ground pin in-hole and SMT Signal pin (female)

96_MMPX-50-0-2/111_N

Environmental data	
Operation temperature	-65 °C ... 155°C

Ordering Information Table			
Item number	Item description	Packaging type	Packaging information
84093966	96_MMPX-50-0-2/111_NM	Tape and Reel	750 pcs/reel
84093961	96_MMPX-50-0-2/111_NM-1	Bulk 10 pcs	Available in blister tape only!

Additional Information	
Remarks	Decoupling tool MMPX shall be used (74_Z-0-0-491/74_Z-0-0-555)!

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P1135 / Date of publication: 25.11.2023 / uncontrolled copy