

Low-noise coax, 75 Ohm, 1 GHz, 85°C, ø5 mm, PVC jacket

G_03130_HT

Properties

- Alternative to standard RG cables
- Low noise
- Coax construction
- 75 Ohm characteristic Impedance



Construction			
Component	Material	Detail	Diameter
Centre conductor	Copper	Wire	0.5 mm
Dielectric	PE (Polyethylene)		3 mm
Semi-conductor	PVC (Polyvinyl chloride)		3.4 mm
Outer conductor	Copper	Braid, 91%	4 mm
Jacket	PVC (Polyvinyl chloride)	RAL 9005 - bk	5 mm +/- 0.15 mm

Electrical data	
Impedance	75 Ω +/-1Ω
Operating frequency	≤ 1 GHz
Capacitance	70.7 pF/m
Insulation resistance	100000000 MΩ*m
Operating Voltage (at sea level)	≤ 2.5 kVrms
Test voltage (50 Hz/1 min)	≤ 5 kVrms
Noise level	≤ 20 mV

Mechanical data	
Weight	approx. 37 g/m
Static bending radius	≥ 25 mm
Repeated bending radius	50 mm

Environmental data	
Operation temperature	-25 °C ... 85 °C
Installation temperature	-20 °C ... 60 °C
Fire characteristics	contains halogene

Low-noise coax, 75 Ohm, 1 GHz, 85°C, ø5 mm, PVC jacket
G_03130_HT

Suitable connectors		
Cable group		U13
Ordering information		
Item number	Item description	Available as assembly only
22510119	G_03130_HT	No

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P1080 / Date of publication: 12.08.2024 / uncontrolled copy