

## Coaxial Cable Connector 11\_4310-50-5-X1/003\_-

### Description

Straight cable plug

Interface standards  
IEC 61169-54



### Technical Data

#### Electrical Data

Impedance	50 $\Omega$
Interface frequency max.	12 GHz

#### Mechanical Data

Centre contact	soldered
Outer contact	soldered
Weight	0.0265 kg

#### Environmental Data

Operating temperature	-55 °C to 90 °C
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant

#### Material Data

Piece Parts	Material	Surface Plating
Centre contact	Brass	Silver Plating
Outer contact	Brass	Silver Plating
Body	Brass	Silver Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating
Gasket	NBR (Nitrile butadiene rubber)	

### Related Documents

Outline drawing	DOU-00259038
Catalogue drawing	DCA-00264957
Assembly instruction	DOC-0000460547

### Ordering Information

Bulk 100 pcs package	11_4310-50-5-X1/003_-H
Single package	11_4310-50-5-X1/003_-E

### Additional Information

Suitable cables	SUCOFORM_250-01_FEP, EZ_250_M17
-----------------	---------------------------------