

Coaxial Cable Connector 16_BNO-0-4-1/133_N

Description

Right angle cable plug

Interface standards
IEC 60169-22



Technical Data

Electrical Data

Impedance	not defined Ω
Interface frequency max.	0.2 GHz

Mechanical Data

Centre contact	soldered
Outer contact	crimped
Weight	0.0216 kg

Environmental Data

Operating temperature	-50 °C to 125 °C
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium / Brass	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating
Gasket	VMQ (Silicone rubber)	
Crimp ferrule	Copper	SUCOPLATE (R) Plating

Related Documents

Outline drawing	DOU-00006030
Catalogue drawing	DOU-00006032
Assembly instruction	DOC-0000179244

Ordering Information

Single package	16_BNO-0-4-1/133_NE
----------------	---------------------

Additional Information

Suitable cables	RG_108_A/U
-----------------	------------